

LANsense I/O and Master/Link cables

- I/O cables for analyser to panel connection
- Master/Link for Master analyser to Link analyser connection

LANsense 액세서리 케이블은 두가지로 분류됩니다:

Master / Link 케이블은 패치존에서 최대 20480포트를 모니터링하기 위한 Star-Wired형 Analyzer 네트워크를 형성하기 위해 Master Analyzer와 Link Analyzer간 직접 연결에 사용 됩니다. 다중 패치 존은 LANsense 데이터베이스 내에서 표현이 가능합니다.

I/O 코드는 LANsense 패치 패널이나 통합 스트립을 Analyzer에 연결하기 위해 사용 됩니다. 12 way 어댑터와 3 x 8 Way 스플리터는 설치된 Analyzer의 포트를 최대한으로 활용하기 위해 사용됩니다.



LANsense I/O and Master/Link cables

CHARACTERISTICS

치수

Mat length

5 m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	이름	Mat length
	N871.CIO005L	-	LANsense I/O Cable LSZH Type C Rev 2 5m	5 (m)
	N871.CIO002L	-	LANsense I/O Cable LSZH Type C Rev 2 2m	2 (m)
	N871.CIO003L	-	LANsense I/O Cable LSZH Type C Rev 2 3m	3 (m)
	N871.CIO010L	-	LANsense I/O Cable LSZH Type C Rev 2 10m	10 (m)
 = Make to order,  = In Stock				

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.