GG45 8C PCB jack

- Right angled Cat 7A PCB jack up to 1500 MHz
- to be used in active equipment or patch panels
- UL94-V0 plastic components
- RoHS compliant
- Wave solder compatible.

자세한 정보와 성능표는 N420.738의 데이터 시트를 참조해 주십시오.





STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

GG45 8C PCB jack

CHARACTERISTICS

구조적 특성	
색상	검은색
스크린	예
Connector type	암
치수	
Depth	21.84 mm
Height	13.5 mm
Width	15.24 mm
사용 특성	
Range	LANmark-7A
Category	Cat. 7A
Component function	Connector

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	이름	Range	Category
	N420.738	-	GG45 Right angle 8 contact jack for PCB mount	LANmark-7A	Cat. 7A

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.