

# Essential-6 Patch Panels

## ESSENTIAL-6 PATCH PANEL 1HU 24 CAT 6 PORTS, REAR CONNECTION, BLACK

**Aginode Ref:** N424.610

- Complies to the latest Category 6 standard
- Punchdown from the rear side
- Unshielded

## Application

The Aginode Essential-6 rear connect panel is based on 19" frame dimensions and has 24 Category 6 RJ45 ports on 1HU. It supports Class E applications up to 250 MHz. When installed in conjunction with Essential-6 cable and outlets, a 25 year Class E Link Certificate can be obtained from the Aginode e-service site.

## Design

The Essential-6 rear connect panel is compatible with the complete Essential-6 range and can be used with all types of UTP Category 6 cable with solid wire from 22 to 24 AWG. The panel comes in smooth painted black and is also available in grey-white finish (N424.600). Transparent label holders are positioned over screen-printed numbering 1-24 which can be covered by included paper labels for customised port identification.

## Performance

The Essential-6 patch panels are compliant with the specifications of ISO/IEC 11801 and IEC 60603-7.

## Installation

- Fast and easy termination of IDC blocks by LSA+ punchdown tooling.
- Wiring according to colour code T568A or T568B.
- An optional cable management support is available for extra strain relief (N424.512).
- Supplied with fixings and tie-wraps.



## STANDARDS

IEC 60603-7-4  
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- For detailed installation instructions, we refer to the Product Manual enclosed with every panel.

Contact resistance:	max. 20 m Ohm
Input to output DC resistance:	max. 200 m Ohm
Insulation resistance:	min. 500 M Ohm
Voltage proof:	1000 V DC or AC peak, contact to contact
Mating cycles:	min. 750
Insertion cycles:	min. 20
Insertion and withdrawal force:	max. 20 N

# Essential-6 Patch panel 1HU 24 Cat 6 ports, rear connection, black

## Characteristics

### 구조적 특성

Connector type	RJ45 및 LSA+ IDC
----------------	-----------------

### 치수

Depth	28.4 mm
Heightunit	1 U

### 사용 특성

Range	essential
Number of ports	24
Category	Cat. 6
Component function	Patch panel

### 문서

[Freetable Cat6 UNSHIELDED connectors additional characteristics.xls xls](#) — 22 KB [다운로드](#) ↓