

LANmark Industry IP65/67 outlets

LANMARK INDUSTRY IP65/67 OUTLET KIT 2 SNAP-IN CATEGORY 6A BLACK

Aginode Ref: N42i.002

LANmark Industry IP67 outlets

산업용 환경과 위험 노출 영역의 LAN을 위한 IP65/67 아웃렛



STANDARDS

ISO/IEC 11801

ISO/IEC 24702

LANmark Industry IP65/67 outlet kit 2 Snap-In Category 6A black

Characteristics

구조적 특성

색상	검은색
스크린	예
Cable entry	상단 또는 밑쪽에서
Material	폴리카보네이트
Connector type	RJ 45

치수

Depth	69 mm
Height	173 mm
Number of screws	4
Width	90 mm
Dimensions of screw	4.00mm
Number of cables	2
Wall thickness	2.5 mm
Approximate weight per piece	0.29 kg
Length cable end on inner side	230.0 mm

전기적 특성

Maximal operating frequency	500 MHz
Characteristic impedance	100 Ohm

기계적 특성

Mechanical resistance to impacts	Normal industrial use
----------------------------------	-----------------------

사용 특성

Electro magnetic interference resistance	Yes
Field of application	Industrial installations
Number of ports	2
Weather resistance	Excellent

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Category	Cat. 6A
Component function	Cabling and Connectivity solutions
Packaging	Box
최대 운용 온도	70 °C
Minimum operating temperature	-40 °C
Water proof	IP 65/67

문서

Freetable LM6A Channel V2 Part 1_1.xls xls — 20.5 KB [다운로드 ↓](#)

Freetable LM6A Channel V2 Part 2_1_1.xls xls — 24.5 KB [다운로드 ↓](#)

판매 및 배송 정보

Includes automatic shutters, 2xCable Glands, 2xLANmark-6A shielded connector, 1xLabelling window. Colour: Black RAL9011