LANmark Industry IP65/67 outlets

LANMARK INDUSTRY IP65/67 OUTLET KIT 2 SNAP-IN CATEGORY 6A BLACK

Aginode Ref: N42i.002

LANmark Industry IP67 outlets

산업용 환경과 위험 노출 영역의 LAN을 위한 IP65/67 아웃렛



STANDARDS

ISO/IEC 11801
ISO/IEC 24702

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark Industry IP65/67 outlet kit 2 Snap-In Category 6A black

Characteristics

구조적 특성	
Cable entry	상단 또는 밑쪽에서
색상	검은색
Connector type	RJ 45
Material	폴리카보네이트
스크린	예
치수	
Approximate weight per piece	0.29 kg
Depth	69 mm
Dimensions of screw	4.00mm
Height	173 mm
Length cable end on inner side	230.0 mm
Number of cables	2
Number of screws	4
Wall thickness	2.5 mm
Width	90 mm
전기적 특성	
Characteristic impedance	100 Ohm
Maximal operating frequency	500 MHz
기계적 특성	
Mechanical resistance to impacts	Normal industrial use
사용 특성	
Category	Cat. 6A
Component function	Cabling and Connectivity solutions
Electro magnetic interference resistance	Yes
Field of application	Industrial installations

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

최대 운용 온도	70 °C
Minimum operating temperature	-40 °C
Number of ports	2
Packaging	Box
Water proof	IP 65/67
Weather resistance	Excellent

문서

Freetable LM6A Channel V2 Part 1_1.xls xls — 20.5 KB 다운로드

Freetable LM6A Channel V2 Part 2_1_1.xls xls — 24.5 KB 다운로드

판매 및 배송 정보

Includes automatic shutters, 2xCable Glands, 2xLANmark-6A shielded connector, 1xLabelling window. Colour: Black RAL9011

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.