Accessories for over head patching frames

PAIR OF PATCH CORD MANAGEMENT HOOKS BLACK FOR OVERHEAD PATCHING FRAMES

Aginode Ref: N345.401

- Pair of Patch Cord Management Hooks for Overhead Patching Frame
- Required to guide patch cords on both sides of the frame
- Easy to mount with 2 screws and cage nuts
- Up to 3 hooks on each side
- Black flexible plastic



STANDARDS

Manufacturer specification

Application

LANmark High-Density racks and frames have been designed to host busy Cross-Connects in data centres. Specific attention has been given to technical constraints of data centres such as cooling and space scarcity. Numerous features contibute to an optimal space utilisation and enable installation on busy data centre floors. These High-Density racks and frames enable excellent front, rear and lateral access. This is of great importance during installation but also during maintenance and upgrade operations. Proper management of large numbers of cords and securing clarity is critical for data centres management and reliability over the life time. Examples of equipment that can be hosted in LANmark High-Density rack and frames are given below:

- Angled panels and accessories
- High Density fibre optic panels
- MPO panels
- LANsense - Intelligent patching
- Suitable for Cat.6A, 7 and 7A
- Suitable for OM3, OM4 and OS2
- EMAC - Environmental control

Performance

LANmark High-Density racks and frames have been designed to host all LANmark fibre optic and copper patch panels.

Installation

These patch cords management hooks are required to guide the cords on both sides of the Overhead Patching Frame. They provide support and help maintaining clarity. They are sold in

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

pairs and can easily be mounted with cage nuts and screws. Up to 3 hooks can be installed on each side of the frame.

When these patch cords management hooks are mounted on both sides of the overhead patching frame, the total width is :
525mm + 2x68mm = 661mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Pair of Patch Cord Management Hooks Black for Overhead Patching Frames

Characteristics

구조적 특성	
Material	Plastic
색상	검은색
치수	
Width	68 mm
Depth	80 mm
Approximate net weight	0.1 kg
Height	25 mm
사용 특성	
Packaging	Plastic bag
Type of cabinet	Cabinet accessory
Range	LANmark

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.