

Essential-5 Cable

ESSENTIAL F/UTP CAT5E 24AWG LSZH REEL IN BOX 305M

Aginode Ref: N100.455

- F/UTP single foil construction
- Complies to latest Cat 5E standards
- Supports Gigabit Ethernet
- Guaranteed performance to 100MHz

Application

Essential-5 cables are the standard 100MHz offering from Aginode. Manufactured and tested to the latest Category 5e specifications defined in the International and American cable standards, they are suitable for voice and data installations for applications up to 100 MHz.

Design

The Essential-5 cables have AWG 24 solid copper wires and comply with IEC 60228.

The cables are available with a Light Grey PVC or an Orange LSZH sheath. Both versions have flame retardant properties compliant with IEC 60332-1.

Performance

Aginode Essential-5 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

[General Installation Guide](#)



STANDARDS

ANSI/TIA-568-C.2
ISO/IEC 11801

Essential F/UTP Cat5e 24AWG LSZH reel in box 305m

Characteristics

구조적 특성

| | |
|---------------|-----------|
| 색상 | 주황색 |
| 스크린 | 알루미늄 호일 |
| 피복 | 저연 할로겐 프리 |
| Type of cable | F/UTP |

치수

| | |
|-----------------------------|----------|
| 무게(근사치) | 40 kg/km |
| 도체지름 | 0.5 mm |
| Diameter over insulation | 1.04 mm |
| Nominal outer diameter (mm) | 6.3 mm |

전기적 특성

| | |
|--------------------------|---------|
| Characteristic impedance | 100 Ohm |
|--------------------------|---------|

기계적 특성

| | |
|---------------------------------|--------|
| Maximum pulling force by laying | 0.1 kN |
|---------------------------------|--------|

Transmission characteristics

| | |
|---------------------------------------|-------------|
| Skew | 45 ns/100m |
| Nominal Velocity of Propagation (NVP) | 68 % |
| Propagation delay, max. 100 MHz | 534 ns/100m |

사용 특성

| | |
|--|-------------|
| Electro magnetic interference resistance | Yes |
| Range | essential |
| Length | 305 m |
| 操作温度范围 | -20...60 °C |
| Category | Cat. 5e |
| Fire load | 460 MJ/km |
| 난연 | IEC 60332-1 |
| Component function | Cable |
| Packaging | Box |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Ambient installation temperature, range

0...50 °C

최소 굽힘 반지름 - 설치시 (장력작용)

48 mm

최소 굽힘 반지름 - 설치 후

30 mm

문서

freetableEssCat5ecable_5_2.xls xls — 17.5 KB [다운로드](#) ↓