

120 System (4.75 inch)

FIBREROUTE 120MM (4.75 INCH) 45° VERTICAL EXTERNAL BEND

Aginode Ref: N350.120FA22A

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Pathway system designed for accommodation of data centre fibre cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- 120mm External bend to raise or lower the pathway to overcome obstacles
- Tough, flame retardant ABS material

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables.

The rigid channel with matching cover protects fibre optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Vertical Bends are used to raise or lower the channel to go over or under obstacles.

All components of the system including the covers can be installed and uninstalled without special tools.

Size:

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

Depth 117mm(4.6")

Length 194mm(7.7")

Width 162mm(6.4")

FIBREROUTE 120mm (4.75 inch) 45° Vertical External Bend

Characteristics

구조적 특성

색상	노란색
Material	ABS

치수

Depth	117 mm
Width	162 mm
Length	194 mm
Approximate net weight	0.3 kg

사용 특성

操作温度范围	-25...60 °C
Storage temperature, range	-45...60 °C