

# LANmark-OF UC PE (Unitube Steel Armoring - Outdoor)

LANMARK-OF UC 12X MULTIMODE 50/125 OM4 PE BLACK

**Aginode Ref:** N167.UCPE12B

UC optical fibre cables

- Outdoor in ducts or direct burial
- Corrugated steel tape armour
- Available in all fibres grades
- Provides full rodent protection

## Description and Application

The construction is suitable for use outdoor in ducts and for direct burial. It consists of a corrugated steel tape armoring providing full rodent protection. It is surrounded by glass yarns. The cable has a HDPE outer jacket.

The loose tube design has a capacity of up to 24 fibres.

Diameter of the fibres is 250 µm. Termination of these fibres is done with splicing of pigtails.

The cable is watertight due to the gel in the loose tube and the watertight glass yarns.

## Construction

Legend accompanying the cross section drawing:

1. Optical fibres (250 µm)
2. Gel
3. Loose tube
4. Reinforced watertight glass yarns
5. Corrugated steel tape armour
6. PE outer jacket with UV resistant additive

## Characteristics

- Outdoor cable for installation in a duct or direct burial
- Designed for termination by splicing
- Central loose tube design



## STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- Corrugated steel protection
- Waterproof structure, rodent resistant and UV-resistant
- Available in all fibre grades
- Available from 4-24 fibres

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-OF UC 12x Multimode 50/125 OM4 PE Black

## Characteristics

### 구조적 특성

Fiber optic type OM4 50/125

### 치수

무게(근사치) 85 kg/km

Number of optical fibres 12

Nominal outer diameter (mm) 8.5 mm

### 기계적 특성

Mechanical resistance to impacts 3 impacts of 5 N.m

Maximum operating pulling force 450 N

Maximum pulling force (IEC 60794-1-2-E1) 1500 N

Crush resistance (IEC 60794-1-E3) 300 N/cm

### 사용 특성

操作温度范围 -40...70 °C

Minimum dynamic operating bending radius 180.0 mm

Minimum static operating bending radius 130 mm

Storage temperature, range -40...70 °C

Ambient installation temperature, range 0...40 °C

## 성과 선언

LANmark-OF UC 12x Multimode 50/125 OM4 PE Black pdf — 140.33 KB [다운로드](#) ↓