

# LANmark-OF UCUN (Unitube Steel Armoring - Universal) Eca

LANMARK-OF UC UNIVERSAL 6X MULTIMODE 50/125 OM4 LSZH ECA BLACK

**Aginode Ref:** N167.UCUN06B

UC optical fibre cables

- Indoor/Outdoor cable
- Corrugated steel tape armour
- Gel filled tube
- All fibre grades
- Provides full rodent protection
- Low Smoke Zero Halogene (LSZH)

## Description and Application

The construction is suitable for indoor/outdoor use. It consists of a corrugated steel tape armouring providing full rodent protection. It is surrounded by glass yarns. The cable has a LSZH outer jacket.

The loose tube design has a capacity of up to 24 fibres.

Diameter of the fibres is 250 um. Termination of these fibres is done with splicing of pigtails.

The cable is watertight due to the gel in the loose tube and the watertight glass yarns.


## Construction

Legend accompanying the cross section drawing:

1. Optical fibres (250 um)
2. Gel
3. Loose tube
4. Reinforced watertight glass yarns
5. Corrugated steel tape armour
6. LSZH outer jacket with UV resistant additive

## Characteristics

- Indoor/Outdoor cable
- Flame retardant (IEC 60332-1 and NFC 32070 C2) and fire retardant (IEC 60332-3 and NFC 32070 C1)
- Designed for termination by splicing



## STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- Central loose tube design
- Corrugated steel protection
- Waterproof structure, rodent resistant and UV-resistant
- Available in all fibre grades
- Available from 4-24 fibres

# LANmark-OF UC Universal 6x Multimode 50/125 OM4 LSZH Eca Black

## Characteristics

### 구조적 특성

|                  |            |
|------------------|------------|
| Fiber optic type | OM4 50/125 |
|------------------|------------|

### 치수

|                             |           |
|-----------------------------|-----------|
| 무게(근사치)                     | 104 kg/km |
| Number of optical fibres    | 6         |
| Nominal outer diameter (mm) | 8.5 mm    |

### 기계적 특성

|  |                    |
|--|--------------------|
| Mechanical resistance to impacts         | 3 impacts of 5 N.m |
| Maximum operating pulling force          | 450 N              |
| Maximum pulling force (IEC 60794-1-2-E1) | 1500 N             |
| Crush resistance (IEC 60794-1-E3)        | 300 N/cm           |

### 사용 특성

|  |             |
|--|-------------|
| 操作温度范围                                   | -40...60 °C |
| Fire retardant                           | IEC 60332-3 |
| Minimum dynamic operating bending radius | 170.0 mm    |
| Minimum static operating bending radius  | 130 mm      |
| 난연                                       | IEC 60332-1 |
| Storage temperature, range               | -40...60 °C |
| Ambient installation temperature, range  | 0...40 °C   |

## 성과 선언

LANmark-OF UC Universal 6x Multimode 50/125 OM4 LSZH Eca Black pdf — 140.73 KB [다운로드](#) ↓