Waterfall & Accessories

FIBREROUTE WATERFALL ASSEMBLY-90MM(3.55 INCH)



Aginode Ref: N350.003SD01A

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Pathway system designed for accommodation of data centre fibre cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Waterfall Assembly to provide transition from Channel to racks or cabinets
- Could attach 1 Flexible tube(N350.003SD10A)
- Tough, flame retardant ABS material

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables .
The rigid channel with matching cover protects fibre optic cables from damage.
All components of the system are made of tough, fire retardant materials.
The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Waterfall Assembly provides an exit for fibre optic cables or cords from the channel into racks or cabinets. The split plastic flex tube is attached to the Waterfall for easy access to the fibre optic cables.

The Waterfall is secured to the channel using T-type screws.

STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

FIBREROUTE Waterfall Assembly-90mm(3.55 inch)

Characteristics

구조적 특성	
색상	노란색
Material	ABS
치수	
Approximate net weight	0.3 kg
사용 특성	
操作温度范围	-25...60 °C
Storage temperature, range	-45...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.