Microduct - Unitube cables

MICROCABLE 1X6SM SP1108 B-LITE

Aginode Ref: SP1108

This unitube cable is used in the Access, Distribution, City Network and FTTx applications; it is designed to be easily installed designed for outdoor installation by blowing in microduct.





Characteristics & Applications

- High blowing distance due to the excellent friction properties of the outer sheath
- Right balance between flexibility and rigidity
- Aramid yarns reinforcement
- All dielectric design
- Waterproof structure

Fibre type

The cable is available with different fibre types.

Construction

- Jelly filled dual wall tube
- Aramid yarns
- Low coefficient of friction sheath

STANDARDS

EN 187000
IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Microcable 1x6SM SP1108 B-LITE

Characteristics

구조적 특성	
색상	녹색
Fiber optic type	SM
Armour type	아라미드
피복	HDPE
Metal free	Yes
구조	Unitube
치수	
Number of tubes	1
무게(근사치)	10 kg/km
Number of optical fibres	6
Nominal outer diameter (mm)	3.3 mm
기계적 특성	
Maximum tensile load during service (Tl)	10.0 daN
Maximum admissible traction load (Tm)	15 daN
Crush resistance (IEC 60794-1-E3)	200 N/cm
사용 특성	
操作温度范围	-30...70 °C
Storage temperature, range	-40...70 °C
Installation type	Outdoor - Microduct blowable
Installation temperature, range	0...40 °C
Bending factor when laying	20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.