

# Distribution - Tight cables Cca

TBU LSZH 6XSM G657A1 SP1857 BK

**Aginode Ref:** 10538572

Tight Buffer cable from 2 to 24- fibres

This tight buffer cable is designed for indoor/outdoor installation.

This cable has an outstanding fire behaviour.

Direct connectorization is made easy with 900µm buffered structure.

This cable can be operated under a large temperature range.

## Design

The TBU LSZH\* SP1857 cable has a central strength member (FRP: Fibre Reinforced Plastic), with 6 900µm buffered structure around. The design is reinforced by a layer of glass yarns and a LSZH\* sheath.

## Fibre type

The TBU LSZH\* SP1857 cable is available with multimode and singlemode fibres.


## Technical performances

The tight buffer cable performances are specified in the following tables.

## Additional details

This cable is provided as a standard with a black sheath, other sheath colours are also available. Long exposure to UV with these other colours could generate colour fading.

\* LSZH: Low Smoke Zero Halogen.



## STANDARDS

EN 50399 B2  
IEC 60332-1  
IEC 60332-3  
IEC 60754-1  
IEC 60794  
IEC 61034  
NF C32-070/C1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# TBU LSZH 6xSM G657A1 SP1857 BK

## Characteristics

### 구조적 특성

색상	검은색
Fiber optic type	SM (G657.A1)
피복	저연 할로겐 프리
Halogen free	IEC 60754-1
Metal free	Yes
Strength member	FRP 센터 보강재
구조	Multi Tight
Additional strength member	유리사

### 치수

무게(근사치)	33 kg/km
Number of optical fibres	6
Cable Diameter, range	... mm
Number of optical fibres, range	...
Nominal outer diameter (mm)	5.3 mm

### 기계적 특성

Mechanical resistance to impacts	10 impacts of 3 N.m
Maximum permanent tensile load	0.2 kN
Crush resistance (IEC 60794-1-E3)	100 N/cm
Maximum installation tension	800 N

### 사용 특성

操作温度范围	-20...70 °C
Fire retardant	IEC 60332-3
Minimum static operating bending radius	55 mm
난연	IEC 60332-1
연기밀도	IEC 61034-2
U.V resistance	Very good
Storage temperature, range	-40...70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Laying operation bending radius	80 mm
Installation type	Indoor/Outdoor
Installation temperature, range	0...40 °C
Water proof	Radial

## 성과 선언

TBU LSZH 6xSM G657A1 SP1857 BK pdf — 119.78 KB 다운로드 ↓

## 판매 및 배송 정보

## Standard Marking

Aginode - FIBRE OPTIC CABLE - TBU LSZH Cca s1a d1 a1 SP1857 - XXxYY - FB - TN - metric

XX = Fibre Count YY = Fibre Type FB = Frameries, Belgium (manufacturing place) TN = Traceability Number