LANmark-7 Cable

LANMARK-7 S/FTP DUAL AWG23 CAT 7 LSZH DCA S2 D1 A1 ORANGE 500M REEL

Aginode Ref: N100.367-OD

- S/FTP cable with individually shielded pairs and global braid
- Exceeds Category 7 ACR with >30dB
- Optimised for use with LANmark-7A GG45 connector
- Easy to install
- Dual version (2 x 4 prs) permits two cables to be installed in one go

Note: product picture showing 4pr version



STANDARDS

EN 50173
EN 50288-4-1
IEEE 802.3bt (PoE++)
ISO/IEC 11801
ISO/IEC 61156-5

Description

LANmark-7 cable has an S/FTP construction with individual pair foils and an overall braid offering superior performance in terms of ACR. It is fully compliant with the Category 7 standards and when installed together with the GG45 LANmark-7A connector, the system is guaranteed to exceed all channel requirements in all configuration scenarios (up to 4-connector channels).

Application

LANmark-7 will support all current and planned data applications developed for cabling up to Class F.

- All Ethernet applications including
- 1000Base-T
- 1000Base-TX
- 10GBase-T
- CATV up to 862MHz
- Any future Class F application

Installation

Ease of Installation is one of the unique features of LANmark-7 cable. Extra attention has been paid to ensure screen coverage is maintained both during and after installation. The cable has been designed specifically to offer both optimum performance and ease of termination when used in conjunction with the LANmark-7A GG45 connector.

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

cable’s print legend.

Electrical Performance LANmark-7 Cable

Frequency (MHz)	Attenuation (dB/100m)		NEXT (in dB)		ACR (in dB)		PS-NEXT (in dB)		ACR-F (in dB)		PS-ACR-F (in dB)		Return Loss (in dB)	
	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.
1,00	4,0	1,8	75,0	100,0	71,0	98,2	72,0	98,0	75,0	98,0	75,0	96,0	20,0	
4,00	4,0	3,5	75,0	100,0	71,0	96,5	72,0	98,0	75,0	98,0	75,0	96,0	23,0	26,0
10,00	5,9	5,5	75,0	100,0	69,1	94,5	72,0	98,0	75,0	98,0	72,3	96,0	25,0	28,0
16,00	7,4	6,8	75,0	100,0	67,6	93,2	72,0	98,0	71,2	96,0	68,2	94,0	25,0	28,0
20,00	8,3	7,7	75,0	100,0	66,7	92,3	72,0	98,0	69,3	94,0	66,3	92,0	25,0	28,0
31,25	10,4	9,6	75,0	100,0	64,6	90,4	72,0	98,0	65,4	90,0	62,4	88,0	23,6	26,0
62,50	14,9	14,0	75,0	100,0	60,1	86,0	72,0	98,0	59,4	84,0	56,4	82,0	21,5	25,0
100,00	19,0	17,7	72,4	100,0	53,4	82,3	69,4	98,0	55,3	75,0	52,3	73,0	20,1	24,0
155,00	24,0	22,8	69,5	96,0	45,6	73,2	66,5	93,0	51,5	70,0	48,5	68,0	18,8	23,0
250,00	31,0	29,0	66,4	94,0	35,5	65,0	63,4	91,0	47,3	66,0	44,3	64,0	17,3	22,0
300,00	34,2	32,1	65,2	92,0	31,1	59,9	62,2	88,0	45,8	54,0	42,8	52,0	17,3	20,0
600,00	50,1	45,5	60,7	90,0	10,6	44,5	57,7	86,0	39,7	54,0	36,7	52,0	17,3	20,0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-7 S/FTP Dual AWG23 Cat 7 LSZH Dca s2 d1 a1 Orange 500m reel

Characteristics

구조적 특성	
스크린	알루미늄 호일 + 주석 도금 구리 브레이드
피복	저연 할로겐 프리
Sheath colour	주황색
Lead free	Yes
Type of cable	S/FTP Shotgun
Drain wire	없음
치수	
무게(근사치)	100 kg/km
Number of pairs	8
Conductor cross-section (AWG/KCMIL)	23
Diameter over insulation	1.42 mm
Nominal outer diameter (mm)	7.0 mm
전기적 특성	
Mutual capacitance	45 nF/km
Characteristic impedance	100 Ohm
Max. transfer impedance at 30 MHz (Ohm/km)	50 Ohm/km
20° C에서 최대 도체 DC저항	80 Ohm/km
기계적 특성	
Maximum operating pulling force	100 N
Transmission characteristics	
Skew	25 ns/100m
Nominal Velocity of Propagation (NVP)	82 %
Coupling attenuation at 30 MHz	>85 dB
Propagation delay, max. 100 MHz	536 ns/100m
사용 특성	

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Range	LANmark-7
Gases corrosivity	IEC 60754-1; IEC 60754-2
Length	500 m
操作温度范围	-20...60 °C
Category	Cat. 7
난연	IEC 60332-1
연기밀도	IEC 61034-2
Packaging	Reel
Ambient installation temperature, range	-10...60 °C
최소 굽힘 반지름 - 설치시 (장력작용)	56 mm
최소 굽힘 반지름 - 설치 후	28 mm

문서

Freetable LM7 600_3.xls xls — 19 KB 다운로드

성과 선언

LANmark-7 S/FTP Dual AWG23 Cat 7 LSZH Dca s2 d1 a1 Orange 500m reel pdf — 141.11 KB 다운로드

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.