

LANmark-6A Cable (International)

LANMARK-6A F/UTP AWG23 CAT 6A LSZH ORANGE 1000M REEL

Aginode Ref: N100.671G

- Ideal cable for 10GBase-T application
- Full compliance to latest standards for Category 6A and Class EA
- Guaranteed performance up to 500MHz
- Global screen offering Alien Crosstalk immunity

Application

LANmark-6A cables are the ideal solution for a 10G Ethernet network. The range has been designed specifically to support the higher frequencies required for 10 Gigabit Ethernet, while maintaining full backwards compatibility with today's needs. All LANmark-6A cables are shielded, in order to ensure immunity to Alien Crosstalk and other external interferences.


- 10Base-T Ethernet
- 100Base-TX Fast Ethernet
- 1000Base-TX Gigabit Ethernet
- 10GBase-T 10 Gigabit Ethernet IEEE 802.3
- 155 Mbit ATM
- 1.2 Gbit ATM
- future Cat 6A and Class EA applications

Performance

With guaranteed performance to 500MHz, Aginode LANmark-6A cables exceed the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

When used in combination with Aginode LANmark-6A Evo connectors and LANmark-6A Ultim patch cords, the system supports the 10GBase-T applications as defined in IEEE 802.3an and meets or exceeds the link and channel requirements for Category 6A and Class EA as defined in TIA/EIA 568-C.2 and ISO/IEC 11801.

Installation



STANDARDS

ANSI/TIA-568-C.2
EN 50173-1
EN 50288-4-1
IEC 61156-5
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

The LANmark-6A cables have the advantage of offering flexibility for installation and termination.

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

Guarantees

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6A cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

Electrical Performance LANmark-6A Cable (International)

| Freq in MHz | Attm in dB | | NEXT in dB | | PSNEXT in dB | | ACR-F in dB | | PS ACR-F in dB | | PS ANEXT in dB | | PS AACR-F in dB | | RL in dB | |
|----------------|---------------|------|---------------|------|-----------------|------|----------------|------|-------------------|------|-------------------|------|--------------------|------|-------------|------|
| | Max | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ |
| 1 | 2.1 | 2.1 | 74.3 | 79.3 | 72.3 | 77.3 | 67.8 | 67.8 | 44.8 | 64.8 | 67.0 | 90.0 | 67.0 | 16.7 | 20.0 | 26.0 |
| 4 | 3.8 | 3.8 | 65.3 | 70.3 | 63.3 | 68.3 | 55.8 | 75.8 | 52.8 | 72.8 | 67.0 | 90.0 | 66.2 | 75.9 | 23.0 | 29.0 |
| 10 | 5.9 | 5.9 | 59.3 | 64.3 | 57.3 | 62.3 | 47.8 | 67.8 | 44.8 | 64.8 | 67.0 | 87.0 | 58.2 | 67.9 | 25.0 | 31.0 |
| 16 | 7.5 | 7.5 | 56.2 | 61.2 | 54.2 | 59.2 | 43.7 | 63.7 | 40.7 | 60.7 | 67.0 | 85.0 | 54.1 | 63.8 | 25.0 | 31.0 |
| 20 | 8.4 | 8.4 | 54.8 | 59.8 | 52.8 | 57.8 | 41.8 | 61.8 | 38.8 | 58.8 | 67.0 | 84.0 | 52.2 | 61.9 | 25.0 | 31.0 |
| 31.25 | 10.5 | 10.5 | 51.9 | 56.9 | 49.9 | 54.9 | 37.9 | 57.9 | 34.9 | 54.9 | 67.0 | 82.1 | 48.3 | 58.0 | 23.6 | 29.6 |
| 62.5 | 15.0 | 15.0 | 47.4 | 52.4 | 45.4 | 50.4 | 31.9 | 51.9 | 28.9 | 48.9 | 65.6 | 79.0 | 42.3 | 52.0 | 21.5 | 27.5 |
| 100 | 19.1 | 19.1 | 44.3 | 49.3 | 42.3 | 47.3 | 27.8 | 47.8 | 24.8 | 44.8 | 65.5 | 77.9 | 38.2 | 47.9 | 20.1 | 26.1 |
| 150 | 25.1 | 25.1 | 41.4 | 46.4 | 39.4 | 44.4 | 24.0 | 44.0 | 21.0 | 41.0 | 59.6 | 74.1 | 34.4 | 44.1 | 19.8 | 24.8 |
| 200 | 27.6 | 27.6 | 39.8 | 44.8 | 37.8 | 42.8 | 21.8 | 41.8 | 18.8 | 38.8 | 58.0 | 72.5 | 32.2 | 41.9 | 18.0 | 24.0 |
| 250 | 31.1 | 31.1 | 38.3 | 43.3 | 36.3 | 41.3 | 19.8 | 39.8 | 16.8 | 36.8 | 56.5 | 71.0 | 30.2 | 39.9 | 17.3 | 23.3 |
| 300 | 34.3 | 34.3 | 37.1 | 42.1 | 35.1 | 40.1 | 18.3 | 38.3 | 15.3 | 35.3 | 55.3 | 69.8 | 28.7 | 38.4 | 16.8 | 22.8 |
| 600 | 45.3 | 45.3 | 33.8 | 38.8 | 31.8 | 36.8 | 13.8 | 33.8 | 10.8 | 30.8 | 52.0 | 66.5 | 24.2 | 33.9 | 15.2 | 21.2 |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-6A F/UTP AWG23 Cat 6A LSZH Orange 1000m reel

Characteristics

구조적 특성

| | |
|---------------|-----------|
| 색상 | 주황색 |
| 피복 | 저연 할로겐 프리 |
| Type of cable | F/UTP |

치수

| | |
|-------------------------------------|---------|
| Conductor cross-section (AWG/KCMIL) | 23 |
| Diameter over insulation | 1.12 mm |
| Nominal outer diameter (mm) | 7.2 mm |

전기적 특성

| | |
|--|------------|
| Mutual capacitance | 45 nF/km |
| Characteristic impedance | 100 Ohm |
| Max. transfer impedance at 30 MHz (Ohm/km) | 120 Ohm/km |
| 20° C에서 최대 도체 DC저항 | 85 Ohm/km |

기계적 특성

| | |
|---------------------------------|-------|
| Maximum operating pulling force | 110 N |
|---------------------------------|-------|

Transmission characteristics

| | |
|---------------------------------------|--------------|
| Skew | 45 ns/100m |
| Attenuation Crosstalk Ratio, 250MHz | 12.2 dB/100m |
| Nominal Velocity of Propagation (NVP) | 67 % |
| Coupling attenuation at 30 MHz | >70 dB |
| Propagation delay, max. 100 MHz | 536 ns/100m |

사용 특성

| | |
|-------------------|--------------------------|
| Range | LANmark-6A |
| Gases corrosivity | IEC 60754-1; IEC 60754-2 |
| 操作温度范围 | -20...60 °C |
| Category | Cat. 6A |
| 난연 | IEC 60332-1 |
| 연기밀도 | IEC 61034 |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Packaging

Reel

Ambient installation temperature, range

-10...60 °C

최소 굽힘 반지름 - 설치시 (장력작용)

60 mm

최소 굽힘 반지름 - 설치 후

30 mm

문서

Freetable LM6A F1UTP V3_2.xls xls — 21 KB [다운로드](#) ↓