

LANmark-6 U/UTP Cable

LANMARK-6 U/UTP AWG23 CAT 6 350MHZ LSZH CCA S1A D1 A1 ORANGE 500M REEL

Aginode Ref: N100.605-OC

- Compliant with all Category 6 cable standards
- Supports Class E applications
- Central cross member maintains geometry and performance
- Tested up to 350MHz
- Enhanced reaction-to-fire performance according to CPR classification Cca-s1a,d1,a1 (h/EN50575:2014+A1:2016)

Application

Aginode LANmark-6 cables are the ideal solution for most of today's network requirements in normal office environments. They are manufactured and tested to the latest Category 6 specifications defined in the International and American cable standards and are designed to meet the quality and performance criteria needed to support all applications up to 250 MHz.


- 10baseT Ethernet
- 100baseTX Fast Ethernet
- 1000baseTX Gigabit Ethernet
- 155 MBit ATM
- 622 MBit ATM
- 1.2 Gbit ATM
- Future class E applications

Design

The LANmark-6 U/UTP cables have a central cross element which helps maintaining the stability of the cable geometry and reduces the risk of a reduction in performance when bending the cable.

The cables are available with a Dark Grey PVC or an Orange LSZH sheath. Both versions have flame retardant properties compliant with IEC 60332-1 and are compliant with EuroClass Eca according to EN50575:2014 +A1:2016.

EuroClass Dca and Cca versions are also available.



STANDARDS

ANSI/TIA-568-C.2
EN 50173-1
EN 50288
IEC 60332-3
IEC 61156-5
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Performance

Tested to 350 MHz and with guaranteed performance to 250 MHz, Aginode LANmark-6 cables exceed the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

Guarantees

The LANmark-6 cable performance is guaranteed to meet or exceed the requirements of the above mentioned standards.

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6 cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

Electrical Performance LANmark-6 U/UTP Cable

Freq. in MHz	IL		NEXT		PSNEXT		ACR-F		PS ACR-F		RL	
	in Db/100m		in dB		in dB		in dB		in dB		in dB	
	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.
1	2,0	2,0	74,3	80,3	72,3	78,3	67,8	72,8	64,8	69,8	20,0	22,0
4	3,8	3,8	65,3	71,3	63,3	69,3	55,8	60,8	52,8	57,8	23,0	25,0
10	6,0	6,0	59,3	65,3	57,3	63,3	47,8	52,8	44,8	49,8	25,0	27,0
16	7,6	7,6	56,2	62,2	54,2	60,2	43,7	48,7	40,7	45,7	25,0	27,0
20	8,5	8,5	54,8	60,8	52,8	58,8	41,8	46,8	38,8	43,8	25,0	27,0
31,25	10,7	10,7	51,9	57,9	49,9	55,9	37,9	42,9	34,9	39,9	23,6	25,6
62,5	15,4	15,4	47,4	53,4	45,4	51,4	31,9	36,9	28,9	33,9	21,5	23,5
100	19,8	19,8	44,3	50,3	42,3	48,3	27,8	32,8	24,8	29,8	20,1	22,1
155	25,2	25,2	41,4	47,4	39,4	45,4	24,0	29,0	21,0	26,0	18,8	20,8
200	29,0	29,0	39,8	45,8	37,8	43,8	21,8	26,8	18,8	23,8	18,0	20,0
250	32,8	32,8	38,3	44,3	36,3	42,3	19,8	24,8	16,8	21,8	17,3	19,3
300	-	36,4	-	43,1	-	41,1	-	23,3	-	20,3	-	18,8
350	-	39,8	-	42,1	-	40,1	-	21,9	-	18,9	-	18,3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-6 U/UTP AWG23 Cat 6 350MHz LSZH Cca s1a d1 a1 Orange 500m reel

Characteristics

구조적 특성

색상	주황색
피복	저연 할로겐 프리
스크린	비차폐
Type of cable	U/UTP

치수

무게(근사치)	46 kg/km
Conductor cross-section (AWG/KCMIL)	23
Diameter over insulation	1.02 mm
Nominal outer diameter (mm)	6.5 mm

전기적 특성

Characteristic impedance	100 Ohm
20° C에서 최대 도체 DC저항	85 Ohm/km
Mutual capacitance	56 nF/km

기계적 특성

Maximum operating pulling force	100 N
---------------------------------	-------

Transmission characteristics

Attenuation Crosstalk Ratio, 250MHz	5.5 dB/100m
Coupling attenuation at 30 MHz	45 dB
Nominal Velocity of Propagation (NVP)	68 %
Propagation delay, max. 100 MHz	536 ns/100m
Skew	30 ns/100m

사용 특성

Ambient installation temperature, range	-10...60 °C
Category	Cat. 6
Field of application	Indoor

Fire retardant	IEC 60332-3
난연	IEC 60332-1
Length	500 m
최소 굽힘 반지름 - 설치시 (장력작용)	52 mm
최소 굽힘 반지름 - 설치 후	26 mm
操作温度范围	-20...60 °C
Packaging	Reel
Range	LANmark-6
연기밀도	IEC 61034

성과 선언

LANmark-6 U/UTP AWG23 Cat 6 350MHz LSZH Cca s1a d1 a1 Orange 500m reel pdf — 140.89 KB [다운로드](#) ↓