

Cat.6 450 F/UTP LSZH Dca

NEX C6 450 F/UTP LSZH DCA 4P 305 RIB IVOIRY

Aginode Ref: 10272113

- Complies to latest Cat 6 standard version
- Supports Class E applications
- Cable tested up to 450 MHz
- Flame retardant according to EN50575:2014+A1:2016 and IEC 60332-1
- Global screen for EMC performance
- Compatible POE, POE+ and UPOE
- RoHS EC Directive compliant
- Compliant with European Reach regulation
- N'Roll and MOBIWAY™ compatible

Application



Les câbles à paires symétriques F/UTP de Catégorie 6 composent l'offre d'entrée de gamme de Nexans. Cette construction, fabriquée selon les exigences des normes IEC 61156-5, représente un composant de choix pour les applications Classe E, telles que : Ethernet, Fast Ethernet, Gigabit Ethernet ... Les câbles F/UTP Cat 6 de Nexans sont idéaux pour les applications VDI jusqu'à 250MHz. Les câbles Nexans Cat.6, associés avec une connectique de même performances, sont idéaux pour les applications VDI selon les normes ISO/IEC 11801, EN 50173 et TIA/EIA 568.

Construction

1. Ame conductrice : Cuivre nu massif
2. Isolation : Polyéthylène (EN 50290-2-23) - Deux fils isolés torsadés en paires
3. Jonc étoile - 4 paires assemblées
4. Fil de continuité cuivre étamé
5. Ecran : Ruban Alu/Pet. Alu à l'intérieur
6. Gaine : LSZH - Dca

Environnement

Conçus pour minimiser l'impact sur l'environnement, les câbles Nexans sont conformes à la Directive RoHS 2011/65 et à la réglementation Reach 1907/2006/EC. La gaine extérieure en matériau sans halogène (IEC 60754-1 / EN 50267-2-1) réduit les



STANDARDS

EN 50173
EN 50288
EN 50575
IEC 60332-1
IEC 61156-5
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

émissions de fumées (IEC 61034-1/2 / EN 50268-1/2) et ne produit pas d'émissions de gaz acide en cas de feu (IEC 60754-2 / EN 50267-2-2).

Nexans mesure l'impact environnemental de chacun de ses produits. Sur demande, l'Eco Material Declaration ou l'Ecopassport peuvent être fournis.

Cat 6 450 F-UTP TRANSMISSION CHARACTERISTICS

CAT.6 450 F/UTP TRANSMISSION CHARACTERISTICS

Values at 20°C

Frequency (MHz)	S/T	4	10	16	20	100	200	250	350	450
Attenuation max. (dB/100m)	Standard	3.8	6.0	7.6	8.5	19.9	29.1	33.0	-	-
	Typical	3.6	5.5	6.9	7.7	17.6	25.4	28.6	34.4	39.5
NEXT min. (dB)	Standard	66.3	60.3	57.2	55.8	45.3	40.8	39.3	-	-
	Typical	80.5	72.7	68.8	66.9	53.3	47.4	45.5	42.7	40.5
PSNEXT min. (dB)	Standard	63.3	57.3	54.2	52.8	42.3	37.8	36.3	-	-
	Typical	77.5	69.7	65.8	63.9	50.3	44.4	42.5	39.7	37.5
ACRF min. (dB)	Standard	56.0	48.0	43.9	42.0	28.0	22.0	20.0	-	-
	Typical	85.5	76.3	71.5	69.3	53.1	46.1	43.9	40.5	38.0
PSACRF min. (dB)	Standard	53.0	45.0	40.9	39.0	25.0	19.0	17.0	-	-
	Typical	82.5	73.3	68.5	66.3	50.1	43.1	40.9	37.5	35.0
Return Loss min. (dB)	Standard	23.0	25.0	25.0	25.0	20.1	18.0	17.3	-	-
	Typical	27.0	29.0	29.0	29.0	24.5	22.5	21.9	20.9	20.2

NEX C6 450 F/UTP LSZH Dca 4P 305 RIB IVOIRY

Characteristics

구조적 특성

피복	저연 할로겐 프리
Sheath colour	아이보리 화이트
Halogen free	예
Higher heating value	821 MJ/km
Type of cable	F/UTP
Overall screen	Aluminium/polyester tape

치수

무게(근사치)	49 kg/km
Number of pairs	4
Conductor cross-section (AWG/KCMIL)	24
Diameter over insulation	1.13 mm
Nominal outer diameter (mm)	7.1 mm
External dimensions	Not applicable

전기적 특성

Mutual capacitance	50 nF/km
20° C에서 최대 도체 DC저항	95 Ohm/km
Characteristic impedance at 100 MHz	100 Ohm

기계적 특성

Maximum installation tension	80 N
------------------------------	------

Transmission characteristics

Nominal Velocity of Propagation (NVP)	70 %
Coupling attenuation at 30 MHz	>50dB

사용 특성

Field of application	Fixed installations
Category	Cat. 6
난연	IEC 60332-1
연기밀도	Low

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Packaging	Reel in a box
Ambient installation temperature, range	0...50 °C
Bending factor when laying	8 (xD)
설치 시 벤딩 요소	4 (xD)
Ambient static operating temperature, range	-20...70 °C

성과 선언

NEX C6 450 F/UTP LSZH Dca 4P 305 RIB IVOIRY pdf — 116.86 KB [다운로드](#) ↓