

# Distribution - Microbundle cables Cca

MB LSZH 8X12SM G657A1 SP1880 BK

**Aginode Ref:** 10542212

Multi Micro-bundles cable - up to 144 fibres

This multi micro-bundles cable is designed for indoor/outdoor usage and can be installed by pulling or blowing thanks to a low friction LSZH outersheath (typical blowing distance 500m)

This cable has an outstanding fire behaviour.

This cable can be operated under a large temperature range.

## Design

The MB LSZH\* SP1880 cable has a central strength member (FRP : Fibre Reinforced Plastic), with max. 12 bundles of 12 fibres each. The design is reinforced by a layer of glass yarns and a LSZH\* sheath.


## Fibre type

The MB LSZH\* SP1880 cable is available with singlemode and multimode fibres.

## Additional details

This cable is provided as a standard with a black sheath, other sheath colours are also available. Long exposure to UV with these other colours could generate colour fading.

\* LSZH: Low Smoke Zero Halogen.



## STANDARDS

EN 50399  
IEC 60332-1  
IEC 60754-1  
IEC 60794  
IEC 61034  
NF C32-070/C2

# MB LSZH 8x12SM G657A1 SP1880 BK

## Characteristics

### 구조적 특성

색상	검은색
Fiber optic type	SM (G657.A1)
피복	저연 할로겐 프리
Halogen free	IEC 60754-1
Metal free	Yes
Strength member	FRP 센터 보강재
구조	멀티 번들 튜브
Additional strength member	유리사

### 치수

Number of tubes	8
무게(근사치)	77 kg/km
Number of optical fibres	96
Cable Diameter, range	5.9...9.3 mm
Number of optical fibres, range	12...144
Nominal outer diameter (mm)	8.4 mm

### 기계적 특성

Mechanical resistance to impacts	10 impacts of 1 N.m
Maximum permanent tensile load	0.45 kN
Crush resistance (IEC 60794-1-E3)	100 N/cm
Maximum installation tension	1750 N

### 사용 특성

操作温度范围	-20...60 °C
Fire retardant	IEC 60332-3
Minimum static operating bending radius	120 mm
난연	IEC 60332-1
연기밀도	IEC 61034-2
U.V resistance	Very good

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Storage temperature, range	-40...60 °C
Laying operation bending radius	150 mm
Installation type	Indoor/Outdoor
Installation temperature, range	0...40 °C
Water proof	Radial

## 성과 선언

MB LSZH 8x12SM G657A1 SP1880 BK pdf — 119.75 KB [다운로드 ↓](#)

## 판매 및 배송 정보

## Standard Marking

Aginode - FIBRE OPTIC CABLE - MB LSZH Cca s1 d1 a1 SP1880 - XXxYY - FB - TN - metric

XX = Fibre Count

YY = Fibre Type

FB = Frameries, Belgium (manufacturing place)

TN = Traceability Number