

# Splicing Patching / COSH144

## COSH 5SU/3U 144 SC LEFT AXIS VERSION

**Aginode Ref:** 10266640

COSH module with combined splicing-patching function

- Height : 5SU/3U
- Compatible with 15mm bending radius
- Full access to the back of the frame
- 144 SC dual adaptors and 144 pigtails
- Fully pre-connectorised

## Application

The COSH144 5SU/3U 19" module with combined splicing and patching functions is used to connect up to 144 fibres. On the terminal part of the FTTH network, the COSH 144 modules receive the fibres located downstream the mutualisation point. The size of the module increases the density by 33% compare to the 4U version.

## Description

The module includes a space reserved for splicing of the incoming fibres. Splicing is performed in splicing trays. A front panel ensures the patching function with a capacity of 144 SC using dual adaptors. The module is compatible with all types of frames (19" or ETSI standards) with a minimum depth 300mm. The accessories fitted with the module guarantee the conformity with the bending radius of the fibre (15 mm). It is prepared in order to minimise the installation time on sites where it is deployed.

The module is composed of the following subparts:

- Fixed chassis attached to the rack (19" or ETSI),
- Swivelling chassis (left or right axis versions available) including a front patch panel with alphanumerical identification for the adaptors,
- Pivoting support for the splice trays,
- Front output jumper management system,
- Device for lateral management of optical jumper harnesses.

The management of cables or protection tubes is done at the rear of the module whilst the management of the jumpers is made at the front and on the rotation axis side.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



## STANDARDS

Aginode specification

# COSH 5SU/3U 144 SC left axis version

## Characteristics

### 구조적 특성

색상 RAL 9002

Cabinet format 19"/ETSI

Material Steel painted

### 치수

Depth 215 mm

Height 125 mm

Number of cassettes 12

Splice number 144

Cable Diameter 5 mm

Heightunit 3 U

Number of connectors 144

### 사용 특성

操作温度范围 -25...70 °C

Adaptor SC/APC

Minimum static operating bending radius 15 mm

Packaging Box

RoHS compliant Yes