# Outlets: @XS-Slim

**@XS-SLIM KIT - INDOOR CABLE 1FO (PULLING)**




**Aginode Ref:** 10272957

- **1 SC adapters**
- Wall mounted, on flush box or DIN rail
- No lid-opening to fix the outlet
- **Ready-to-fix** kit in option
- **1 Keystone slot** for RJ45 or coaxial plug delivered within the Hybrid optional kit

Optical terminal outlets, installed in the subscriber's home, are the optical equipments materializing the demarcation between the FTTH operator network and the local subscriber's network.

Compact and ergonomic, its design has been studied in **partnership with SismoDesign agency** for a sober, discreet and elegant depiction, to fit at best at the inhabitant.

For security, adapters include an **automatic laser and dust protection**, called « internal shutter ».

The front side contains all the necessary indications (from top to bottom):

- Swiveling flap to protect and hide the identification label
- Area to stick Identification Label (under the flap)
- Indication that polarizing slot is upwards
- Integrated laser symbol

The @XS-Slim outlets range comes in 2 families:

- The "equipped" outlet is provided with adapter and pigtail preinstalled. It must then be connected with the subscriber's cable.
- The "kit" outlet is provided pre-cabled, ready to be fastened without any outlet opening. Cable type and length are customizable.

## STANDARDS

Aginode specification
Orange/France Telecom

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# @XS-Slim Kit - Indoor cable 1FO (pulling)

## Characteristics

| | |
|---|---|
| **구조적 특성** | |
| Material | Thermoplastic |
| 색상 | 하얀색 RAL 9010 |
| **치수** | |
| Width | 80 mm |
| Splice number | 2 |
| Maximum number of adaptators | 1 |
| Depth | 25 mm |
| Cable Diameter, range | 2...5 mm |
| Cable length | 30 m |
| Height | 80 mm |
| **기계적 특성** | |
| IK Rating | 5 |
| **사용 특성** | |
| Packaging | Box |
| U.V resistance | Yes |
| 操作温度范围 | -5...45 °C |
| Minimum static operating bending radius | 11 mm |
| Fire resistant | UL 94 V0 |
| Adaptor | SC/APC |
| Watertightness | IP 50 |

### 문서

Installation @XS-Hybrid/Slim pdf — 2.53 MB 다운로드

ESERV_PTOCablesStd_EN_1.xlsx xlsx — 10.27 KB 다운로드

@XS-FAST pdf — 981.89 KB 다운로드

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*