

LANmark-6A Cable

LANMARK-6A F1/UTP AWG23 CAT 6A LSZH CCA S1A D1 A1 ORANGE 1000M REEL

Aginode Ref: N100.622G-OC

- Ideal cable for 10GBase-T application
- Full compliance to latest standards for Category 6A and Class EA
- Guaranteed performance up to 500MHz
- Global screen offering Alien Crosstalk immunity
- Foil with aluminium side facing outwards providing easy bonding with connector
- Enhanced reaction-to-fire performance according to CPR classification Cca-s1a,d1,a1 (h/EN50575:2014+A1:2016)

Application

LANmark-6A cables are the ideal solution for a 10G Ethernet network. The range has been designed specifically to support the higher frequencies required for 10 Gigabit Ethernet, while maintaining full backwards compatibility with today's needs. All LANmark-6A cables are shielded, in order to ensure immunity to Alien Crosstalk and other external interferences.

- 10Base-T Ethernet
- 100Base-TX Fast Ethernet
- 1000Base-TX Gigabit Ethernet
- 10GBase-T 10 Gigabit Ethernet IEEE 802.3
- 155 Mbit ATM
- 1.2 Gbit ATM
- future Cat 6A and Class EA applications
- PoE++ Type 4 (IEEE 802.3bt)

Performance

With guaranteed performance to 500MHz, Aginode LANmark-6A cables exceed the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568.2-D

When used in combination with Aginode LANmark-6A connectors and LANmark-6A Ultim patch cords, the system supports the 10GBase-T applications as defined in IEEE 802.3an and meets or exceeds the link and channel



STANDARDS

ANSI/TIA 568.2-D
EN 50173-1
IEC 61156-5
IEEE 802.3bt (PoE++)
ISO/IEC 11801
EN 50288

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

requirements for Category 6A and Class EA as defined in TIA/EIA 568.2-D and ISO/IEC 11801.

Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable’s print legend.

Guarantees

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6A cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

Electrical Performance LANmark-6A F1/UTP Cable

| Freq in MHz | AttN in dB | | NEXT in dB | | PSNEXT in dB | | ACR-F in dB | | PS ACR-F in dB | | PS ANEXT in dB | | PS AACR-F in dB | | RL in dB | |
|----------------|---------------|------|---------------|------|-----------------|------|----------------|------|-------------------|------|-------------------|------|--------------------|------|-------------|------|
| | Max | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ | Min | Typ |
| 1 | 2.1 | 2.1 | 74.3 | 79.3 | 72.3 | 77.3 | 67.8 | 67.8 | 64.8 | 64.8 | 67.0 | 90.0 | 67.0 | 79.7 | 20.0 | 26.0 |
| 4 | 3.8 | 3.8 | 65.3 | 70.3 | 63.3 | 68.3 | 55.8 | 75.8 | 52.8 | 72.8 | 67.0 | 90.0 | 66.2 | 75.9 | 23.0 | 29.0 |
| 10 | 5.9 | 5.9 | 59.3 | 64.3 | 57.3 | 62.3 | 47.8 | 67.8 | 44.8 | 64.8 | 67.0 | 87.0 | 58.2 | 67.9 | 25.0 | 31.0 |
| 16 | 7.5 | 7.5 | 56.2 | 61.2 | 54.2 | 59.2 | 45.7 | 65.7 | 42.7 | 60.7 | 67.0 | 85.0 | 54.1 | 63.8 | 25.0 | 31.0 |
| 20 | 8.4 | 8.4 | 54.8 | 59.8 | 52.8 | 57.8 | 41.8 | 61.8 | 38.8 | 58.8 | 67.0 | 84.0 | 52.2 | 61.9 | 25.0 | 31.0 |
| 31.25 | 10.5 | 10.5 | 51.9 | 56.9 | 49.9 | 54.9 | 37.9 | 57.9 | 34.9 | 54.9 | 67.0 | 82.1 | 48.3 | 58.0 | 23.8 | 29.6 |
| 62.5 | 15.0 | 15.0 | 47.4 | 52.4 | 45.4 | 50.4 | 31.9 | 51.9 | 28.9 | 48.9 | 65.6 | 79.0 | 42.3 | 52.0 | 21.5 | 27.5 |
| 100 | 19.1 | 19.1 | 44.3 | 49.3 | 42.3 | 47.3 | 27.8 | 47.8 | 24.8 | 44.8 | 62.5 | 77.0 | 38.2 | 47.9 | 20.1 | 26.1 |
| 155 | 24.1 | 24.1 | 41.4 | 46.4 | 39.4 | 44.4 | 24.0 | 44.0 | 21.0 | 41.0 | 59.8 | 74.1 | 34.4 | 44.1 | 18.8 | 24.8 |
| 200 | 27.6 | 27.6 | 39.8 | 44.8 | 37.8 | 42.8 | 21.8 | 41.8 | 18.8 | 38.8 | 58.0 | 72.5 | 32.2 | 41.9 | 18.0 | 24.0 |
| 250 | 31.1 | 31.1 | 38.3 | 43.3 | 36.3 | 41.3 | 19.8 | 39.8 | 16.8 | 36.8 | 56.5 | 71.0 | 30.9 | 39.9 | 17.3 | 23.3 |
| 300 | 34.3 | 34.3 | 37.1 | 42.1 | 35.1 | 40.1 | 18.3 | 38.3 | 15.3 | 35.3 | 55.3 | 69.8 | 28.7 | 38.4 | 16.8 | 22.8 |
| 600 | 45.3 | 45.3 | 33.8 | 38.8 | 31.8 | 36.8 | 13.8 | 33.8 | 10.8 | 30.8 | 52.0 | 66.5 | 24.2 | 33.9 | 15.2 | 21.2 |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



LANmark-6A F1/UTP AWG23 Cat 6A LSZH Cca s1a d1 a1

Orange 1000m reel

Characteristics

구조적 특성

| | |
|---------------|-----------|
| 색상 | 주황색 |
| 피복 | 저연 할로겐 프리 |
| Type of cable | F/UTP |

치수

| | |
|-------------------------------------|----------|
| 무게(근사치) | 52 kg/km |
| Conductor cross-section (AWG/KCMIL) | 23 |
| Diameter over insulation | 1.2 mm |
| Nominal outer diameter (mm) | 7.5 mm |

전기적 특성

| | |
|--|------------|
| Characteristic impedance | 100 Ohm |
| 20° C에서 최대 도체 DC저항 | 80 Ohm/km |
| Max. transfer impedance at 30 MHz (Ohm/km) | 120 Ohm/km |
| Mutual capacitance | 45 nF/km |

기계적 특성

| | |
|---------------------------------|-------|
| Maximum operating pulling force | 100 N |
|---------------------------------|-------|

Transmission characteristics

| | |
|---------------------------------------|-------------|
| Coupling attenuation at 30 MHz | >70 dB |
| Nominal Velocity of Propagation (NVP) | 68 % |
| Propagation delay, max. 100 MHz | 536 ns/100m |
| Skew | 45 ns/100m |

사용 특성

| | |
|---|--------------------------|
| Ambient installation temperature, range | -10...60 °C |
| Category | Cat. 6A |
| 난연 | IEC 60332-1 |
| Gases corrosivity | IEC 60754-1; IEC 60754-2 |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

| | |
|------------------------|-------------|
| Length | 1000 m |
| 최소 굽힘 반지름 - 설치시 (장력작용) | 60 mm |
| 최소 굽힘 반지름 - 설치 후 | 30 mm |
| 操作温度范围 | -20...60 °C |
| Packaging | Reel |
| Range | LANmark-6A |
| 연기밀도 | IEC 61034 |

문서

Freetable LM6A F1UTP V3_2.xls xls — 21 KB [다운로드](#) ↓

성과 선언

LANmark-6A F1/UTP AWG23 Cat 6A LSZH Cca s1a d1 a1 Orange 1000m reel pdf — 141.61 KB [다운로드](#) ↓