

# Duct - Microbundle cables

MICROBUNDLE RSM CABLE 6X6SM SP1825

**Aginode Ref:** 10526093


This ruggedized cable is used for Access, Distribution, City Network and FTTx applications. It is designed to be quickly installed by pulling, blowing and on aerial

## Characteristics & Applications

- Ruggedized cable design
- Easy installation with mid span access possibility
- Easy micro bundle stripability
- Glass yarns and radial strength members reinforcement
- All dielectric design
- Waterproof structure

## Construction

- Jelly filled microbundles containing coloured fibres
- Radial FRP strength members
- Glass yarns reinforcement
- Water swellable tape
- HDPE outer sheath



## STANDARDS

EN 187000  
IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# Microbundle RSM cable 6x6SM SP1825

## Characteristics

### 구조적 특성

Fiber optic type	SM (G657.A2)
Armour type	유리 섬유사
피복	HDPE
Sheath colour	Black - UV
Metal free	Yes
Strength member	Embedded FRP
구조	멀티 번들 튜브

### 치수

Number of tubes	6
무게(근사치)	60 kg/km
Number of optical fibres	36
Nominal outer diameter (mm)	8.6 mm

### 기계적 특성

Maximum admissible traction load (Tm)	188 daN
Crush resistance (IEC 60794-1-E3)	250 N/cm

### 사용 특성

操作温度范围	-30...70 °C
Storage temperature, range	-40...70 °C
Installation type	Outdoor - Duct
Ambient installation temperature, range	0...40 °C
Bending factor when laying	20 (xD)