
# Floor Patching: @XS-BOX M

**@XS-BOX M PATCHING V0**



- Indoor patching and splicing box
- Patching version 8 connectors and a storage space
- Splicing and patching version with up to a maximum splice capacity of 24 OF (with LC duplex)
- Output for drops up and down
- Installation vertically or horizontally
- Aesthetic and ergonomic

## STANDARDS

IEC 61753-1

The @XS-BOX M line is designed to manage the building distribution of a riser cable to subscribers as part of FTTH deployments.

**Main functions :**

- Clamping of riser cable Ømax 14mm to right or left* with open cable protection and on-demand fiber extraction management
- Clamping of up to 8 SC or LC Duplex preterminated drop cables
- Management of excess lengths with storage space
- Horizontal or vertical wall mounting by screws (provided) inside or outside the housing

**Composition :**

The @XS-BOX M is built around a base and a cover, to which are added the cassettes and a façade with connectors answering to the selected wiring architecture.
Optionally, it can incorporate 2 ¼ turn screws to secure the closure.

**Cabling :**

The @XS-BOX M is optimized for extraction installation, but it is also compatible with termination and midspan configurations.
In the body, various zones of coiling make it possible to

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

manage bundles and 900µm fibers connected or waiting to avoid any incident when connecting a new subscriber.

This  patching configuration allows a connection of up to 16 subscribers on demand (using LC duplex),

with a connection of the subscribers on demand in 2 trays of capacity 12* spliceseach compatible fibers G652D / G657A.
* These cassettes are compatible with mechanical splices and ANT

## Gas-stop / EZA integration

@XS-BOX M is able to manage up to 2 Gas-stop for clamping duct (up to 14 mm) as shown below :

##image:112874:center##

## Accessory - Cover extension kit

##image:110716##

These covers are used to fix the @XS-BOX M along a PVC cable way to have a perfect finish by hiding drop and riser cables.

The kit is composed with 2 covers for up and down.

Aginode reference : **10192633**

## Accessory - Sealing kit

##image:110717##

These sealing is used to have a better protection regarding dust and water, it gives to the @XS-BOX M an IP level at IP42.

The kit is composed with 4 sealing, 2 small for riser and 2 wider for drops to protect up and down.

Aginode reference : **10179110**

## Accessory - Wall spacer

##image:110718##

These sealing is used to have a better protection regarding dust and water, it gives to the @XS-BOX M an IP level at IP42.

The kit is composed with 4 sealing, 2 small for riser and 2 wider for drops to protect up and down.

Aginode reference : **10179110**

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# @XS-BOX M Patching V0

## Characteristics

| | |
|---|---|
| **구조적 특성** | |
| Fiber optic type | SM (G.652D) |
| **치수** | |
| Depth | 42 mm |
| Height | 180 mm |
| Width | 125 mm |
| **기계적 특성** | |
| IK Rating | 8 |
| **사용 특성** | |
| 操作温度范围 | -10...60 °C |
| Fire resistant | UL 94 V0 |
| Watertightness | IP 52 |

### 문서

@XS-BOX M splicing and patching notice pdf — 4.19 MB 다운로드

### 판매 및 배송 정보

Unit packaging in plastic bag

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*