
TDCOP - Optical modular cable head

TDCOP 144 SC/APC FOR BREAKOUT APPLICATION

Aginode Ref: 10261142

Optical modular cable head

- High-density - 12 plates with 12 adaptors each
- Light weight
- 12 SC/APC adaptors
- Cable storage and clamp
- Working position locking system



STANDARDS

Aginode specification
Orange/France Telecom

Optical Modular Cable Head TDCO is a solution designed for high density nodes of FTTx networks where an important flexibility to route the optical signal is requested.

This thermoplastic version gives a significant reduction of weight, over 50% compared with metal version (less than 5 kg with a plastic version equipped with 144 fibers), improves flexibility with individual management of 12 fibers plates, maintains excellent sturdiness, and proposes many innovations as a locking in the working position.

Main functions are:

- To protect up to 144 optical fibers against environment and handling,
- To coil and identify effectively and easily the optical fibers,
- To distribute up to 12 fibers per plate.

TDCOP consists in a frame equipped with 12 plates with covers. Each plate has a 12-fibre modularity. Accessories for fibers management (combs, clamps, sealings…) are provided.

This is the version for preterminated cables :

Breakout application: Each plate includes without accessory 12 SC adapters.

Each plate has a two coiling areas: a first one for coiling up to 2 meters of cable and a second one protected by a transparent cover to store cables outputs. Each plate has a dedicated area to splice up to 12 pigtails.

Fixation is performed with a metal fixed chassis on an optical open frame. The metal chassis also provides rotation axis of

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

the plates, guiding ways for Ø5mm tubes or cables from the rear, guiding ways for Ø2mm patchcords from the front to the left hand side.

Splice cassette with 12 FO capacity can be added in case of need (repair etc...)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

TDCOP 144 SC/APC for breakout application

Characteristics

구조적 특성	
색상	담회색 RAL 7035
Halogen free	예
Material	Thermoplastic
치수	
Depth	260 mm
Height	250 mm
Width	272 mm
Cable Diameter	5 mm
사용 특성	
操作温度范围	-25...70 °C
Adaptor	SC/APC
Minimum static operating bending radius	30 mm
Packaging	Box
RoHS compliant	Yes

문서

Optical modular cable head - Installation manual - version C pdf — 8.81 MB 다운로드

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.