Duct - Unitube cables

UNITUBE CABLE 1X12SM SP1647

Aginode Ref: 10231297

This unitube cable is used in the Access, Distribution, City Network and FTTx applications; it is designed to be easily installed in outdoor installations.





Characteristics & Applications

- Easy installation due to the friction properties of the outer sheath
- Robust design
- Waterproof structure
- Halogen free

Fibre type

The cable is available with different fibre types.

Construction

- Jelly filled tube
- Reinforcement elements
- Low friction outer sheath

STANDARDS

IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Unitube Cable 1x12SM SP1647

Characteristics

구조적 특성	
색상	검은색
Fiber optic type	SM (G.652D)
Armour type	유리 섬유사
피복	HDPE
구조	Unitube
Dielectric	예
치수	
Number of tubes	1
무게(근사치)	40 kg/km
Number of optical fibres	12
Nominal outer diameter (mm)	6.9 mm
기계적 특성	
Maximum admissible traction load (Tm)	180 daN
사용 특성	
操作温度范围	-30...70 °C
Storage temperature, range	-40...70 °C
Installation type	Outdoor - Duct
Installation temperature, range	0...40 °C
Bending factor when laying	20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.