

Duct - Microbundle cables

MICROBUNDLE RSM CABLE 1X12SM SP1849


This ruggedized cable is used for Access, Distribution, City Network and FTTx applications. It is designed to be quickly installed by pulling, blowing and on aerial

Characteristics & Applications

- Ruggedized cable design
- Easy installation with mid span access possibility
- Easy micro bundle stripability
- Glass yarns and radial strength members reinforcement
- All dielectric design
- Waterproof structure

Construction

- Jelly filled microbundles containing coloured fibres
- Radial FRP strength members
- Glass yarns reinforcement
- Water swellable tape
- HDPE outer sheath



STANDARDS

EN 187000
IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Microbundle RSM cable 1x12SM SP1849

Characteristics

구조적 특성

Fiber optic type	SM
Armour type	유리 섬유사
피복	HDPE
Sheath colour	Black - UV
Metal free	Yes
Strength member	Embedded FRP
구조	멀티 번들 튜브

치수

Number of tubes	1
무게(근사치)	45 kg/km
Number of optical fibres	12
Nominal outer diameter (mm)	7.8 mm

기계적 특성

Maximum admissible traction load (Tm)	108 daN
Crush resistance (IEC 60794-1-E3)	250 N/cm

사용 특성

操作温度范围	-30...70 °C
Storage temperature, range	-40...70 °C
Installation type	Outdoor - Duct
Ambient installation temperature, range	0...40 °C
Bending factor when laying	20 (xD)