

# Aerial Metallic Self Supported ULW

ULW 2X12 SP1922 (PIA)

This cable is used for Access, Distribution, City Network and FTTx applications. It is designed for installation in the BT Fibre Network in Overhead and Underground environments.

The cable is design to respond to the British Telecommunications Specifications CW1842 and related specifications CW1500 part 2, 7 and 11.

Maximum spans 68m.

## Characteristics & Applications

- Metallic strength members
- Microbundles inside - easy to open without special tools
- Waterproof dry core structure
- Small size design to minimize the effect of ice and wind
- Fully compatible with the reference BT toolings for cable opening
- Breaking load < 2000N

## Fibre Type

Compliant with BT CW1505 Cat2 and ITU-T G657A1

## Construction

- Jelly filled microbundles containing coloured fibres
- Swellable yarns
- HDPE outer sheath with embedded metallic brass coated steel wires
- Colour : Black outer sheath with 2 yellow stripes at 180°



## STANDARDS

Customer specification  
IEC 60793  
IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# ULW 2x12 SP1922 (PIA)

## Characteristics

### 구조적 특성

Fiber optic type	SM
피복	HDPE
Metal free	No
Strength member	Steel rods
구조	멀티 번들 튜브

### 치수

Number of tubes	2
무게(근사치)	34 kg/km
Number of optical fibres	24
Nominal outer diameter (mm)	7.0 mm

### 기계적 특성

Maximum admissible traction load (Tm)	65 daN
Impact resistance (EN 187 000)	10 J
Crush resistance (IEC 60794-1-E3)	200 N/cm

### 사용 특성

Rodent protection	No
操作温度范围	-20...70 °C
Storage temperature, range	-40...70 °C
Installation type	Aerial - self-supporting
Ambient installation temperature, range	0...40 °C
Bending factor when laying	20 (xD)

### 문서

Tableau de charge aérien ULW\_3.xlsx xlsx — 12.17 KB [다운로드](#) ↓

### 판매 및 배송 정보

MARKING in accordance with BT specification CW1402 : (LASER+PHONE) FB WWYY COF215 ULTRA LIGHT WEIGHT OH FIBRE CABLE 24F/21 PROPERTY OF BT (LASER+PHONE) N°OF CCCCCM

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.