

Essential-6 Cable

ESSENTIAL-6 U/UTP CAT 6 LSZH 23AWG 305M REEL IN BOX

Aginode Ref: N100.170

- Unshielded construction
- Complies to latest Category 6 standards
- Central cross maintains geometry and performance
- Supports Class E applications up to 250 MHz.

Application

The Aginode Essential-6 cables are manufactured and tested to the latest Category 6 specifications. They are compatible with the complete Essential-6 modular and PCB connectivity range. When the cable is installed in conjunction with Essential-6 outlets and patch panels, a 25 year Class E Link Certificate can be obtained from the Aginode website.

Performance

Aginode Essential-6 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

Values given for 2-connector channel, built with Essential-6 cable, outlet and patch panel. (Values specified at 20°C)



STANDARDS

ANSI/TIA-568-C.2
EN 50288
IEC 61156-5
ISO/IEC 11801-1

Essential-6 U/UTP Cat 6 LSZH 23AWG 305m reel in box

Characteristics

구조적 특성

피복 저연 할로겐 프리

Type of cable U/UTP

색상 주황색

치수

Conductor cross-section (AWG/KCMIL) 23

Nominal outer diameter (mm) 6.1 mm

Diameter over insulation 1.0 mm

전기적 특성

Max. DC resistance of the conductor at 20°C (Ohm/km) 93.8

Mutual capacitance 56 nF/km

Characteristic impedance 100 Ohm

기계적 특성

Maximum operating pulling force 100 N

Transmission characteristics

Propagation delay, max. 100 MHz 536 ns/100m

Skew 45 ns/100m

사용 특성

Packaging Reel in a box

Field of application Indoor

操作温度范围 -20...60 °C

최소 굽힘 반지름 - 설치시 (장력작용) 49 mm

최소 굽힘 반지름 - 설치 후 25 mm

연기밀도 IEC 61034

Ambient installation temperature, range -10...60 °C

Category Cat. 6

Range essential-6

Length 305 m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

문서

Freetable Ess6 channel.xls xls — 14 KB [다운로드 ↓](#)