

LANmark-6 Cable

LANMARK-6 U/UTP LSZH IEC 60332-3-24 305M REEL

Aginode Ref: N100.604FR

- Complies to all Category 6 cable standards
- Supports all Class E applications
- Central cross member maintains geometry and performance
- Tested up to 350MHz
- Fire retardant according to IEC 60332-3-24

Application

Aginode LANmark-6 cables are the ideal solution for most of today's network requirements in normal office environments. They are manufactured and tested to the latest Category 6 specifications defined in the International and American cable standards and are designed to meet the quality and performance criteria needed to support all applications up to 250 MHz.

- 10baseT Ethernet
- 100baseTX Fast Ethernet
- 1000baseTX Gigabit Ethernet
- 155 MBit ATM
- 622 MBit ATM
- 1.2 Gbit ATM
- Future class E applications

Design

The LANmark-6 cables have AWG 23 solid copper wires. The central cross filler helps maintaining the stability of the cable geometry and reduces the risk of a reduction in performance when bending the cable. The cables has fire retardant properties compliant with IEC 60332-3-24.

Performance

Tested to 350 MHz and with guaranteed performance to 250 MHz, Aginode LANmark-6 cables exceed the requirements of the International, European and American cable standards,



STANDARDS

ANSI/TIA-568-C.2
EN 50173-1
IEC 60332-3
IEC 61156-5
ISO/IEC 11801-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

Guarantees

The LANmark-6 cable performance is guaranteed to meet or exceed the requirements of the above mentioned standards.

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6 cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

Electrical Performance LANmark-6 Cable

Freq. in MHz	IL in Db/100m		NEXT in dB		PSNEXT in dB		ACR-F in dB		PS ACR-F in dB		RL in dB	
	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.
1	2,0	2,0	74,3	80,3	72,3	78,3	67,8	72,8	64,8	69,8	20,0	22,0
4	3,8	3,8	65,3	71,3	63,3	69,3	55,8	60,8	52,8	57,8	23,0	25,0
10	6,0	6,0	59,3	65,3	57,3	63,3	47,8	52,8	44,8	49,8	25,0	27,0
16	7,6	7,6	56,2	62,2	54,2	60,2	43,7	48,7	40,7	45,7	25,0	27,0
20	8,5	8,5	54,8	60,8	52,8	58,8	41,8	46,8	38,8	43,8	25,0	27,0
31,25	10,7	10,7	51,9	57,9	49,9	55,9	37,9	42,9	34,9	39,9	23,6	25,6
62,5	15,4	15,4	47,4	53,4	45,4	51,4	31,9	36,9	28,9	33,9	21,5	23,5
100	19,8	19,8	44,3	50,3	42,3	48,3	27,8	32,8	24,8	29,8	20,1	22,1
155	25,2	25,2	41,4	47,4	39,4	45,4	24,0	29,0	21,0	26,0	18,8	20,8
200	29,0	29,0	39,8	45,8	37,8	43,8	21,8	26,8	18,8	23,8	18,0	20,0
250	32,8	32,8	38,3	44,3	36,3	42,3	19,8	24,8	16,8	21,8	17,3	19,3
300	-	36,4	-	43,1	-	41,1	-	23,3	-	20,3	-	18,8
350	-	39,8	-	42,1	-	40,1	-	21,9	-	18,9	-	18,3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-6 U/UTP LSZH IEC 60332-3-24 305m reel

Characteristics

구조적 특성

피복	저연 할로겐 프리 난연
스크린	비차폐
Type of cable	U/UTP
색상	주황색

치수

Conductor cross-section (AWG/KCMIL)	23
Nominal outer diameter (mm)	6.6 mm
Diameter over insulation	1.02 mm

전기적 특성

20° C에서 최대 도체 DC저항	85 Ohm/km
Mutual capacitance	56 nF/km
Characteristic impedance	100 Ohm

기계적 특성

Maximum operating pulling force	100 N
---------------------------------	-------

Transmission characteristics

Propagation delay, max. 100 MHz	536 ns/100m
Nominal Velocity of Propagation (NVP)	67 %
Skew	45 ns/100m
Coupling attenuation at 30 MHz	45 dB
Attenuation Crosstalk Ratio, 250MHz	5.5 dB/100m

사용 특성

Packaging	Reel
操作温度范围	-20...60 °C
최소 굽힘 반지름 - 설치시 (장력작용)	52 mm
최소 굽힘 반지름 - 설치 후	26 mm
연기밀도	IEC 61034
Ambient installation temperature, range	-10...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Category

Cat. 6

Range

LANmark-6

Fire retardant

IEC 60332-3-24 (cat C)

난연

IEC 60332-1

문서

Freetable LM6 cables_Family_2.xls xls — 23 KB [다운로드](#) ↓