

LANmark-OF TB OFNP 2-48C - APAC Region

LANMARK-OF TIGHT BUFFER INDOOR 4X MULTIMODE 50/125 BI OM4 PLENUM, OFNP

Aginode Ref: N177.021NP

- Tight Buffer Indoor optical fiber cables Indoor cable
- Aramid yarns for ease of installation
- Design for direct termination and splicing
- 4 fibers
- Bending Insensitive Fibers for OM4 cables

Application

The LANmark-OF Tight buffer Indoor has 900 um buffered fibres. This second coating till 900 um provides additional protection of the fibres and facilitates the handling when terminating the fibres in a patch panel. The easy strip tight buffer design allows stripping the fibre over 10 cm in one action. The LANmark-OF Tight buffer Indoor is most suitable for direct termination by either anaerobic or hot melt connectors. The tight buffered fibres can also be terminated with splicing of pigtails. The dry structure of the LANmark-Of Tight Buffer Indoor allows both vertical and horizontal installations. It complies with the indoor fibre requirements. The cables can also be installed in a duct by pulling.

Construction

Legend accompanying the cross section drawing:

1. Optical fibre (900 um)
2. Aramid Yarns
3. Outer sheath in PVC OFNP material



STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

LANmark-OF Tight Buffer Indoor 4x Multimode 50/125 BI OM4 Plenum, OFNP

Characteristics

구조적 특성

색상	초록색
Fiber optic type	OM4 50/125

치수

외경	4.8 mm
Weight	21 g
Number of optical fibres	4

기계적 특성

Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Maximum pulling force (IEC 60794-1-2-E1)	460 N

사용 특성

操作温度范围	-20...60 °C
Minimum dynamic operating bending radius	96.0 mm
Minimum static operating bending radius	48 mm
Storage temperature, range	-30...70 °C
Installation temperature, range	0...40 °C