
LANmark-OF TB OFNP 2-48C - 아시아 태평양 지역

LANMARK-OF 타이트 버퍼 실내용 8X 단일모드 9/125 G.657.A1 플레넘, OFNP



Aginode Ref: N17A.023NP

- 타이트 버퍼 실내용 광섬유 케이블, 실내용 케이블
- 설치가 용이한 아라미드 원사
- 직접 종단 및 접합이 가능한 설계
- 8가닥
- 단일 모드 OS2 G.657.A1 케이블용 굽힘에 강한 광섬유

적용 분야

LANmark-OF Tight buffer Indoor 제품은 900 um 버퍼 코팅이 적용된 광섬유를 사용합니다. 이 두 번째
900 um까지 이어지는 이 코팅층은 광섬유를 추가로 보호해 주며,
패치 패널에서 광섬유를 종단 처리할 때 취급이 용이합니다. 쉽게 벗겨지는 타이트 버퍼 설계 덕분에 한 번의 동작으로 10cm 이상의 광섬유를 스트리핑할 수 있습니다.
LANmark-OF 타이트 버퍼 실내용 제품은
무산소 또는 핫멜트 커넥터를 사용하여 직접 종단 처리하는 데 가장 적합합니다. 타이트 버퍼 광섬유는
피그테일 접합을 통해 종단 처리할 수 있습니다.
LANmark-OF 타이트 버퍼 실내용의 건식 구조는 수직 및
수평 설치가 모두 가능합니다. 이 제품은 실내용 광섬유 요구 사항을 준수합니다. 또한 이 케이블은
는 당김 방식을 통해 덕트에 설치할 수도 있습니다.

구조

단면도 설명:

1. 광섬유 (900 um)
2. 아라미드 원사
3. PVC OFNP 소재의 외부 피복

STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF 타이트 버퍼 실내용 8x 단일모드 9/125 G.657.A1 플레넘, OFNP

Characteristics

구조적 특성	
Fiber optic type	SM (G657.A1)
색상	노란색
치수	
Number of optical fibres	8
외경	5.6 mm
Weight	30 g
기계적 특성	
Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Maximum pulling force (IEC 60794-1-2-E1)	460 N
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
사용 특성	
Installation temperature, range	0...40 °C
Storage temperature, range	-30...70 °C
操作温度范围	-20...60 °C
Minimum dynamic operating bending radius	112.0 mm
Minimum static operating bending radius	56 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.