

XPLORER™

XPLORER™ - PATCHING 4U

- Swivelling 4U module for patching
- Up to 144 SC and LC connections
- 19" racks and cabinets
- Manufactured with fibre reinforced composite

The swivelling 4U module pivots around the axis of the fixed chassis. It is locked on the other side. The depth of the panels is reduced to 230mm based on the pivoting concept.

The rear of the 4U panel rotates open to have easy access to the splice cassettes. After splicing the rear is closed again so that the splice cassettes are protected by a cover.

The panels are symmetrical and can be configured as left or right swivelling modules.



STANDARDS

IEC 61753-1

Material and usage characteristics

The panels are made of fibre reinforced composite. This makes the panels more robust compared to traditional metal panels.

The panels are resistant against corrosion, Fungi, UV and the most important aggressive chemicals.

The reduced weight of the panel of around 3,2kg allows the panel to be installed by a single technician.

Density and adaptors

Different connector types and densities are supported. The maximum density is 144 fibre connections for SC and LC connectivity. The SC adaptors have translucent dust caps to allow for visual fault locator so that for instance subscribers and optical channels can be easily identified. The power reduction of the translucent dust caps is 3.5 dB. The LC

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

adaptors have White dust caps that block the laser light.

Fixing of the breakouts

The panel is supplied with 2 fixing kits for break-outs with tie wraps:

- break-out fixed in the fixed chassis
- break-outs fixed in the swivelling module

The overlengths of the break-out legs can be arranged into management rings.

Patching

The adaptors are organized in 12 columns of each 12 adaptors. Letters from “A” to “L” identify the vertical columns. The horizontal adaptor rows are numbered from “1” to “12”.

The patch cords are guided per column to the bottom of the panel. An integrated patch cord guide routes the cords to the pivoting axis.

The panel is delivered with a spool kit. It is fixed on the side of the rack with metal cage nuts. The spool kit manages the cords nicely in the cabinet.

Panel fixing

The panels are fixed inside racks with 9,5mm square slots with sockets and pawns that are toolless installed from the front. The fixed chassis and the lock are fixed on the front rail of the cabinets and for enhanced stability during pivoting the fixed chassis on a support rear rail.

Metal cage nuts for 8,3mm and 9,5mm square slots are also supplied.

Green solution

Panels based on fibre reinforced composite have a significant lower environmental impact, especially during production.


The packaging and the protections inside the box are made of cardboard only. This results in a reduced volume of waste and

easy treatment.

Available products XPLOER™ 4U - Patching

SAP-number	Description
13200109	XPLOER™ Patching Grade B 4U 144xSC/APC
13200110	XPLOER™ Patching Grade B 4U 144xLC/APC

Dimensions XPLOER™ 4U



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

XPLORER™ - Patching 4U

Characteristics

구조적 특성

색상	담회색 RAL 7035
Cabinet format	19"
Material	Thermoplastic

치수

Depth	185 mm
Cable Diameter, range	5...19 mm
Heightunit	4 U

사용 특성

操作温度范围	-40...75 °C
Fire retardant	UL94-V0
Minimum static operating bending radius	30 mm
Chemical resistance	Hydrocarbons resistant
Function	Patching
U.V resistance	Yes

문서

- XPLORER 1U installation manual - Splice and patch pdf — 5.69 MB [다운로드 ↓](#)
- XPLORER 1U installation manual - Splitter pdf — 5.45 MB [다운로드 ↓](#)
- XPLORER 1U installation manual - Patching pdf — 3.72 MB [다운로드 ↓](#)
- XPLORER 1U installation manual - Storage pdf — 6.21 MB [다운로드 ↓](#)
- XPLORER 3U installation manual - Splitter pdf — 6.86 MB [다운로드 ↓](#)
- XPLORER 4U installation manual - Patching pdf — 15.49 MB [다운로드 ↓](#)
- XPLORER 4U installation manual - Splice and patch pdf — 17.55 MB [다운로드 ↓](#)
- XPLORER 4U installation manual - Splice and patch - 3 large splice cassettes pdf — 4.48 MB [다운로드 ↓](#)
- XPLORER 1U installation manual - Splice, patch and splitter pdf — 7.1 MB [다운로드 ↓](#)
- Eco-design at Aginode - FTTH case study pdf — 1.49 MB [다운로드 ↓](#)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

판매 및 배송 정보

Delivery units - 1U : 72 units per palet - 3U and 4U : 20 units per palet