
# Power To The Antenna D-CORE - Eca (N2XCY)

**POWER TO THE ANTENNA D-CORE - ECA 4MM²**

Power To The Antenna D-CORE is a shielded dual conductor power cable. It can be used as a DC power cable for the interconnexion between Base Unit and Radio Units on mobile towers or rooftops. The D-shape of the isolated conductors enables to reduce the diameter and weight of these cables with no negative impact on the properties. It also has best-in-class flexibility.



### Applications

- Power cable 0.6/1.0 kV
- For indoor/outdoor applications
- Used on mobile phone masts

### Cable construction

1. Bare conductor strand - Class 5
2. Insulation (IEC 60811-1)XLPE
3. Longitudinal ALU/PET tape
4. Tinned copper braid (Coverage US >65%)
5. Outer sheath: HFFR - Black - Eca (EN50575)

### Environment

Designed to reduce the environment impact, Aginode cables are compliant with RoHS 2011/65 Directive and European Reach 1907/2006/EC regulation.

## D-CORE Picture



## STANDARDS

EN 50575
IEC 60228
IEC 60332-1
IEC 60502-1

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# Power To The Antenna D-CORE - Eca 4mm²

## Characteristics

| | |
|---|---|
| **구조적 특성** | |
| 스크린 | 폴리에스테르 밴드 - 주석 도금 구리 브레이드 |
| 피복 | 저연 할로겐 프리 |
| Sheath colour | 검은색 |
| Wire colour | Blue - Brown |
| 도체 재료 | Bare copper class 5 |
| 절연 | XLPE |
| **치수** | |
| 무게(근사치) | 170 kg/km |
| 외경 | 11 mm |
| 코어수 | 2 |
| 도체 단면적 | 4 $mm^2$ |
| Diameter over insulation, range | 3.9...4.1 mm |
| **전기적 특성** | |
| 20° C에서 최대 도체 DC저항 | 5.09 Ohm/km |
| Minimum insulation resistance | 10 MOhm.km |
| Breakdown voltage Vcc, 5 min. | 3500.0 V |
| **사용 특성** | |
| Gases corrosivity | IEC 60754-1; IEC 60754-2 |
| 操作温度范围 | -40...90 °C |
| 난연 | IEC 60332-1 |
| 연기밀도 | EN/IEC 61034-2 |
| Packaging | Drum 500 m |
| Storage temperature, range | -40...50 °C |
| Bending factor when laying | 8 (xD) |
| 설치 시 벤딩 요소 | 4 (xD) |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*