

Outlets: @XS-Fast

OUTLETS: @XS-FAST

Aginode Ref: TBD

- Up to 2 SC/LC adapters
- Wall mounted, on flush box, on a DIN rail and on most of the electrical equipment mounting supports on the market
- No lid-opening to fix the outlet
- Ready-to-fix kit in option

Application

By default, it is designed for flush wall mounting. It can also be adapted for use with DIN rails and most standard electrical mounting systems available on the market by means of an optional adapter plate. The @XS-FAST can additionally serve as a DTIO, acting as the termination point of the operator's access network.

Functional characteristics

The OTO can be installed with a pre-connected drop cable entering from either side, the bottom, or the rear. It features a dedicated splicing area and fibre management zone, enabling cable-to-cable or cable-to-pigtails splicing.



STANDARDS

Aginode specification

Outlets: @XS-FAST

Characteristics

구조적 특성

색상	하얀색 RAL 9010
Material	Thermoplastic

치수

Depth	18 mm
Height	80 mm
Maximum number of adaptators	2
Splice number	2
Width	80 mm

기계적 특성

IK Rating	5
-----------	---

사용 특성

Adaptor	SC/LC
Fire resistant	UL 94 V0
Minimum static operating bending radius	15 mm
操作温度范围	-5...45 °C
Packaging	Paper bag
U.V resistance	Yes
Watertightness	IP 50

ABS 1594 -FAST PTO.pdf pdf — 981.89 KB [다운로드](#) ↓