

Essential-6 Cable

ESSENTIAL-6 U/UTP AWG23 CAT 6 LSZH GB 31247 B1 (D0,T0,A1) DARK GREY 305M/REEL

Aginode Ref: N100.170-GB1-D

- Compliant with all Category 6 cable standards
- Supports Class E applications
- Central cross member maintains geometry and performance
- 23AWG conductor size
- GB 31247 B1 (d0,t0,a1) compliance

Application


The Aginode Essential-6 cables are manufactured and tested to the latest Category 6 specifications. They are compatible with the complete Essential-6 modular and PCB connectivity range. When the cable is installed in conjunction with Essential-6 outlets and patch panels, a 25 year Class E Link Certificate can be obtained from the Aginode website.

Performance

Aginode Essential-6 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.



STANDARDS

ANSI/TIA-568-C.2
EN 50173-1
EN 50288
GB 31247
IEC 61156-5
ISO/IEC 11801-1

Essential-6 U/UTP AWG23 CAT 6 LSZH GB 31247 B1 (d0,t0,a1) Dark Grey 305M/Reel

Characteristics

구조적 특성

| | |
|---------------|-----------|
| 색상 | Dark Grey |
| 피복 | 저연 할로겐 프리 |
| Type of cable | UTP |

치수

| | |
|-------------------------------------|--------|
| Conductor cross-section (AWG/KCMIL) | 23 |
| Diameter over insulation | 1.0 mm |
| Nominal outer diameter (mm) | 6.2 mm |

전기적 특성

| | |
|--|----------|
| Mutual capacitance | 56 nF/km |
| Characteristic impedance | 100 Ohm |
| Max. DC resistance of the conductor at 20°C (Ohm/km) | 93.8 |

기계적 특성

| | |
|---------------------------------|-------|
| Maximum operating pulling force | 100 N |
|---------------------------------|-------|

Transmission characteristics

| | |
|---------------------------------|-------------|
| Skew | 45 ns/100m |
| Propagation delay, max. 100 MHz | 536 ns/100m |

사용 특성

| | |
|---|-----------------------|
| Range | essential |
| Field of application | Indoor |
| Length | 305 m |
| 操作温度范围 | -20...60 °C |
| Category | Cat. 6 |
| 난연 | GB31247 B1 (d0.t0.a1) |
| 연기밀도 | IEC 61034-2 |
| Packaging | Drum |
| Ambient installation temperature, range | 0...50 °C |
| 최소 굽힘 반지름 - 설치시 (장력작용) | 50 mm |
| 최소 굽힘 반지름 - 설치 후 | 25 mm |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.