

# 월드롭 V2

## 월드롭 창문 보호 클립

**Aginode Ref:** 13200411 - 14500789

- Aginode 파사드 솔루션의 일부
- 광선로 절단 지점에서 케이블 보호
- 광케이블 추출 과정 중 월드롭 박스와 함께 제공
- 파사드의 실외 사용을 위해 설계
- 재사용 가능

창문 보호 클립은 아지노드 파사드 솔루션의 일부입니다. 이 클립은 섬유 추출 과정에서 WALLDROP 파사드 박스와 함께 제공됩니다.

두 개의 플라스틱 부품으로 구성됩니다:

- 섬유와 케이블 클램핑 장치를 지지하는 파사드 분배 케이블 뒤에 배치되는 한 부분(자외선 차단 플라스틱 타이 제공)

- 4개의 클립으로 액세서리를 닫을 수 있도록 하는 두 번째 부품

창문 보호 클립은 WALLDROP 파사드 박스와 동일한 씰링 시스템을 사용합니다. 따라서 6~12mm의 파사드 케이블과 호환됩니다(6~8, 8~10 및 10~12mm 범위를 커버하는 슬롯 씰 3세트). 이 레퍼런스는 10~12mm의 파사드 케이블용 씰을 통합합니다(케이블 직경이 다른 애플리케이션은 당사에 문의하세요).

최대 100mm까지 케이블을 개방하여 수밀성을 보장합니다.

보호 등급으로 인해 외벽에 사용할 수 있습니다(IP55 / IK07).

이 액세서리는 향후 개입이 필요한 경우 다시 연결할 수 있다는 장점이 있습니다.



### STANDARDS

Aginode specification

# 월드롭 창문 보호 클립

## Characteristics

### 구조적 특성

|          |               |
|----------|---------------|
| 색상       | 검은색           |
| Material | Thermoplastic |

### 치수

|                          |            |
|--------------------------|------------|
| Diameter branch cable    | 3...7 mm   |
| Diameter main cable      | 10...12 mm |
| Height                   | 33 mm      |
| Length                   | 177 mm     |
| Max. number of cables    | 1          |
| Max. number of cassettes | 1          |
| Splice number            | 12         |
| Width                    | 28 mm      |

### 기계적 특성

|           |   |
|-----------|---|
| IK Rating | 7 |
|-----------|---|

### 사용 특성

|                                         |             |
|-----------------------------------------|-------------|
| Installation type                       | Outdoor     |
| Minimum static operating bending radius | 15 mm       |
| 操作温度范围                                  | -40...65 °C |
| Packaging                               | Box         |
| RoHS compliant                          | Yes         |
| U.V resistance                          | Yes         |
| Watertightness                          | IP 55       |

## 문서

Instruction manual pdf — 5.25 MB [다운로드](#) ↓

Leaflet Facade Solution EN pdf — 5.07 MB [다운로드](#) ↓

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.