# LANmark-OF Loose Tube Universal 6 -12 and 24FO - Cca

**LANMARK-OF LOOSE TUBE UNIVERSAL 12XSINGLEMODE 9/125 OS2 LSZH CCA YELLOW**

**Aginode Ref:** N164.LTUN12-YC

- Loose Tube Universal optical fibre cable with High Level of transmission : OS2
- High fire behavior : reaction to fire Cca according to EN50575:2014+A1:2016
- Indoor/Outdoor cable
- Designed for splicing with pigtails



## STANDARDS

ISO/IEC 11801

The new 12FO OS2 Loose Tube technology from Aginode is specifically engineered for indoor building & outdoor where installations where both high performance and fire safety are essential. Designed with a loose tube construction, it offers good protection for fibers against mechanical stresses and environmental factors.

- **CPR (Cca, s2, d1, a1 )**: Low fire propagation, reduced smoke emission, minimal toxic gas release.
- **Loose Tube Gel-Filled Design**: Excellent protection against mechanical stress, water ingress, and temperature variations.
- **Vertical installations with loop reserve** for simplified maintenance and future upgrades.
- **Indoor & Outdoor Application:** Ideal for structured cabling in residential, commercial, and public buildings, as well as outdoor environments.
- **High Performance OS2**: Reliable, high-speed data transmission over long distances.
- **Flexible and Robust**: Easy to install in ducts, conduits, and technical spaces.
- **UV-Resistant & Waterproof**: Designed to withstand outdoor conditions when required.

The central tube contains 12 fibers well identified to make installation easy and simple.

**Applications :**

- Building backbone networks
- Data centers
- Outdoor duct installations

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-OF Loose Tube Universal 12xSinglemode 9/125 OS2 LSZH Cca Yellow

## Characteristics

| | |
|---|---|
| **구조적 특성** | |
| 구조 | 루즈 튜브 |
| Fiber optic type | SM (G657.A1) |
| Halogen free | IEC 60754-1 |
| Jacket material | LSZH Halogen free flame retardant |
| Material used for longitudinal water tightness | Swellable Glass yarns |
| **치수** | |
| 무게(근사치) | 71 kg/km |
| Nominal outer diameter (mm) | 7.6 mm |
| Number of optical fibres | 12 |
| Number of tubes | 1 |
| Tube diameter | 2.3 mm |
| **기계적 특성** | |
| Crush resistance (IEC 60794-1-E3) | 1500 N/100mm |
| Maximum pulling force (IEC 60794-1-2-E1) | 2000 N |
| Tensile strength | 2000 N |
| **사용 특성** | |
| Fire retardant | IEC 60332-3 |
| 난연 | IEC 60332-1-2 |
| Gases corrosivity | IEC 60754-2 |
| Installation temperature, range | -30...60 °C |
| Minimum dynamic operating bending radius | 152 mm |
| Minimum static operating bending radius | 114 mm |
| 操作温度范围 | -40...70 °C |
| 연기밀도 | IEC 61034-2 |
| Storage temperature, range | -40...70 °C |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

| | |
|---|---|
| U.V resistance | Very good |

## DoP: Declaration of Performance

DOP_LANmark-OF Loose Tube Universal 12xSinglemode 9/125 OS2 LSZH Cca Yellow.pdf pdf — 59.19 KB 다운로드

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*