LANmark-OF UCUN (스틸 아머링 - 유니버설) Dca

LANMARK-OF UC UNIVERSAL 12X MULTIMODE 50/125 OM4 LSZH DCA BLACK

Aginode Ref: N167.UCUN12B

UC optical fibre cables

- Provides full rodent protection
- Corrugated steel tape armoring for crush and rodent protection
- Central jelly-filled tube construction
- All fibre grades
- Black LSZH UV-resistant outer sheath – CPR (Dca -s2, d2, a1) rated
- Suitable for indoor and outdoor applications





The UC optical fibre cable from Aginode is specifically designed for installations where mechanical resistance, fibre bandwidth performance, and environmental durability are critical. Its gel-filled and corrugated steel armoring provide robust protection in demanding indoor and outdoor conditions.

- **Armored Design**: Corrugated steel tape for excellent resistance to mechanical stress, crushing, and rodent attacks.
- **Loose Tube Construction**: Central PBT tube filled with thixotropic gel ensures long-term fibre stability.
- **Indoor & Outdoor Application**
- **High Performance OM4**: Optimized for high-speed multimode transmission over medium distances (50/125 µm).
- **Halogen-Free Flame Retardant Jacket**: Low emission of smoke and toxic gases; UV-resistant for extended durability.

The central tube contains up to 24 fibres, color-coded for fast and reliable splicing.

STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF UC Universal 12x Multimode 50/125 OM4 LSZH Dca Black

Characteristics

구조적 특성	
Fiber optic type	OM4
Halogen free	IEC 60754-1
Jacket material	LSZH Halogen free flame retardant
Material used for longitudinal water tightness	Swellable Glass yarns
치수	
무게(근사치)	82 kg/km
Nominal outer diameter (mm)	7.6 mm
Number of optical fibres	12
Number of tubes	1
Tube diameter	2.8 mm
기계적 특성	
Crush resistance (IEC 60794-1-E3)	1500 N/100mm
Tensile strength	1500 N
사용 특성	
난연	IEC 60332-1-2
Gases corrosivity	IEC 60754-2
Installation temperature, range	-30...60 °C
Minimum dynamic operating bending radius	152 mm
Minimum static operating bending radius	114 mm
操作温度范围	-40...70 °C
연기밀도	IEC 61034-2
Storage temperature, range	-40...70 °C
U.V resistance	Very good

DoP: Declaration of Performance

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

DOP_UCUN_12XMM50 OM4_Dca.pdf pdf — 59.14 KB 다운로드

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.