

LANmark-OF Loose Tube Universal 6 -12 and 24FO - Cca

LANMARK-OF LOOSE TUBE UNIVERSAL 12XMULTIMODE 50/125 OM4 LSZH CCA AQUA

Aginode Ref: N167.LTUN12-AC

- Loose Tube Universal optical fibre cable with high level transmission : OM4
- High fire behavior : reaction to fire Cca according to EN50575:2014+A1:2016
- Indoor/Outdoor cable
- Designed for splicing with pigtails

The new 12FO OM4 Loose Tube technology from Aginode is specifically engineered for indoor building & outdoor where installations where both high performance and fire safety are essential. Designed with a loose tube construction, it offers good protection for fibers against mechanical stresses and environmental factors.

- **CPR (Cca, s2, d1, a1)**: Low fire propagation, reduced smoke emission, minimal toxic gas release.
- **Loose Tube Gel-Filled Design**: Excellent protection against mechanical stress, water ingress, and temperature variations.
- **Vertical installations with loop reserve** for simplified maintenance and future upgrades.
- **Indoor & Outdoor Application**: Ideal for structured cabling in residential, commercial, and public buildings, as well as outdoor environments.
- **High Performance OM4** : Reliable, high-speed data transmission over long distances.
- **Flexible and Robust**: Easy to install in ducts, conduits, and technical spaces.
- **UV-Resistant & Waterproof**: Designed to withstand outdoor conditions when required.

The central tube contains till 12 fibers well identified to make installation easy and simple.

Applications :

- Building backbone networks
- Data centers
- Outdoor duct installations



STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF Loose Tube Universal 12xMultimode 50/125 OM4 LSZH Cca Aqua

Characteristics

구조적 특성

| | |
|--|-----------------------------------|
| 구조 | 루즈 튜브 |
| Fiber optic type | OM4 50/125 |
| Halogen free | IEC 60754-1 |
| Jacket material | LSZH Halogen free flame retardant |
| Material used for longitudinal water tightness | Swellable Glass yarns |

치수

| | |
|-----------------------------|----------|
| 무게(근사치) | 71 kg/km |
| Nominal outer diameter (mm) | 7.6 mm |
| Number of optical fibres | 12 |
| Number of tubes | 1 |
| Tube diameter | 2.3 mm |

기계적 특성

| | |
|--|--------------|
| Crush resistance (IEC 60794-1-E3) | 1500 N/100mm |
| Maximum pulling force (IEC 60794-1-2-E1) | 2000 N |
| Tensile strength | 2000 N |

사용 특성

| | |
|--|---------------|
| Fire retardant | IEC 60332-3 |
| 난연 | IEC 60332-1-2 |
| Gases corrosivity | IEC 60754-2 |
| Installation temperature, range | -30...60 °C |
| Minimum dynamic operating bending radius | 152 mm |
| Minimum static operating bending radius | 114 mm |
| 操作温度范围 | -40...70 °C |
| 연기밀도 | IEC 61034-2 |
| Storage temperature, range | -40...70 °C |
| U.V resistance | Very good |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.