LANmark-OF UC PE(유니튜브 스틸 아머링)

LANMARK-OF UC 6X MULTIMODE 50/125 OM3 PE BLACK

Aginode Ref: N165.UCPE06B

UC optical fibre cables

- Outdoor in ducts or direct burial
- Corrugated steel tape armour
- Available in all fibres grades
- Provides full rodent protection



Description and Application

The construction is suitable for use outdoor in ducts and for direct burial. It consists of a corrugated steel tape armouring providing full rodent protection. It is surrounded by glass yarns. The cable has a HDPE outer jacket.
The loose tube design has a capacity of up to 24 fibres.
Diameter of the fibres is 255 um. Termination of these fibres is done with splicing of pigtails.
The cable is watertight due to the gel in the loose tube and the watertight glass yarns.

STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF UC 6x Multimode 50/125 OM3 PE Black

Characteristics

구조적 특성	
구조	루즈 튜브
Fiber optic type	OM3 50/125
Halogen free	예
Jacket material	Polybutylene Terephthalate (PBT)
Material used for longitudinal water tightness	Swellable Glass yarns
치수	
무게(근사치)	64 kg/km
Nominal outer diameter (mm)	7.6 mm
Number of optical fibres	6
Number of tubes	1
Tube diameter	2.8 mm
기계적 특성	
Crush resistance (IEC 60794-1-E3)	2000 N/100mm
Tensile strength	2000 N
사용 특성	
Installation temperature, range	-30...70 °C
操作温度范围	-40...70 °C
연기밀도	IEC 61034-2
Storage temperature, range	-40...70 °C
U.V resistance	Very good

DoP : Declaration of Performance

DOP_UC 6xMM50 OM3 BK.pdf pdf — 58.99 KB 다운로드

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.