# DCmark Rack Unit Solution Collocation DC

**DCMARK RACK UNIT SOLUTION COLLOCATION DC 42U 2 COMPARTMENTS**





**Aginode Ref:** NRL2.420808340-B

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

Rack are equipped with 2 compartment of 20U; each have a single front perforated door, lockable by key. Each key have a specific number for the confidentiality.

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

The Rack NRCL2 is equipped with 2 compartments of 20U with a total loading capacity of 1500Kg. Each compartment have a single front perforated door and double rear perforated door.

To ensure a high confidentiality of the tenant, each compartment have is own key with a specific number printed on the barrel (Aginode is the only part knowing the correspondace between this code and the key number).

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# DCmark Rack Unit Solution Collocation DC 42U 2 compartments

## Characteristics

| | |
|---|---|
| **구조적 특성** | |
| Cabinet format | 19" |
| Compartment number | 2x20U |
| 색상 | 검은색 |
| Cable entry | Entrée supérieure via passe-fil balai et chemin de câble fermé |
| Material | 스틸 |
| Rack version | Collocation |
| Type of front door | Simple porte AV perforée |
| Type of rear door | Double porte AR perforée |
| **치수** | |
| 19'' mounting | Avant & Arrière |
| Compartment Height U | 20U |
| Height | 2017 mm |
| Width | 800 m |
| Approximate net weight | 128 kg |
| Depth | 800 mm |
| Heightunit | 42 U |
| **기계적 특성** | |
| IK Rating | 07 |
| **사용 특성** | |
| Locking system | Clé individuelle par compartiment |
| IP Rating | IP20 |
| Key type | Numéro spécifique & unique |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*