

DCmark Rack Unit Solution Collocation DC

DCMARK RACK UNIT SOLUTION COLLOCATION DC 42U 2 COMPARTMENTS

Aginode Ref: NRL2.420808340-B

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

Rack are equipped with 2 compartment of 20U; each have a single front perforated door, lockable by key. Each key have a specific number for the confidentiality.

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

The Rack NRCL2 is equipped with 2 compartments of 20U with a total loading capacity of 1500Kg. Each compartment have a single front perforated door and double rear perforated door.

To ensure a high confidentiality of the tenant, each compartment have is own key with a specific number printed on the barrel (Aginode is the only part knowing the correspondance between this code and the key number).

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.



DCmark Rack Unit Solution Collocation DC 42U 2 compartments

Characteristics

구조적 특성

Cabinet format	19"
Cable entry	from the top through brush panel and closed duct
색상	검은색
Compartment number	2x20U
Material	스틸
Rack version	Collocation
Type of front door	Single perforated door 80%
Type of rear door	double perforated at 80%

치수

19" mounting	front & rear
Approximate net weight	128 kg
Compartment Height U	20U
Depth	800 mm
Height	2017 mm
Heightunit	42 U
Width	800 m

기계적 특성

IK Rating	07
-----------	----

사용 특성

IP Rating	IP20
Key type	specific number
Locking system	Individual key per compartment