
essential-OF TB LSZH 48-96C - 아시아태평양 지역

ESSENTIAL-OF 타이트 버퍼 LSZH SM G.652.D 48C 노란색

Aginode Ref: N274.TBIN48Y

밀착형 버퍼 광섬유 케이블

- 백본/수평 배선을 위해 설계된 실내용 케이블
- OM3 및 단일모드 G.652.D 규격으로 제공
- 외피는 저연무 무할로겐(LSZH) 소재



?? ?? ? ??

Essential-OF TB ??? ????? ??, ?? ?? ? ??? ?? ???????. ? ??? ???? 900?m ??? ??? ???? ?????. ???? ???? ??? ???? ??? , ??? ??? ?? ??? ?? LSZH ??? ?? ????. Essential-OF TB? ??? ?? OM3 ? ???? G.652.D ???? ?????.

? ??? ???? ?? ?? ?? ??? ??? ?? ??? ?? ????. ? ???? ?? ?? ?? ?? ??? ???? ?? ??? ??? ? ????.

- ?? ? ?? ?? ?? ??
- ?? ???? ? ???? ???? ?? ??
- LSZH ??
- ??? ??? ???

STANDARDS

ANSI/TIA-568-C.3
IEC 60332-1
IEC 60332-3-24
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

essential-OF 타이트 버퍼 LSZH SM G.652.D 48C 노란색

Characteristics

구조적 특성	
Fiber optic type	SM (G.652)
색상	노란색
치수	
Number of optical fibres	48
외경	14.8 mm
기계적 특성	
Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Maximum pulling force (IEC 60794-1-2-E1)	1500 N
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
사용 특성	
Installation temperature, range	0...40 °C
Storage temperature, range	-20...60 °C
操作温度范围	-20...60 °C
Minimum dynamic operating bending radius	296 mm
Minimum static operating bending radius	148 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.