LANmark-OF DB 실외용 PE 2-144코어 APAC 지역

LANMARK-OF 실외용 DB 광케이블, 단일모드 G.652.D 9/125 96F, PE, 검정색, APAC 지역

Aginode Ref: N174.96DBPE

- 덕트 내 설치 또는 매설에 적합한 실외용 제품
- 방수 소재를 적용한 견고한 구조
- OM3/OM4/G.652.D/G.657.A1 규격의 광섬유 제공, 최대 144 코어
- 이중 금속 테이프 외피로 설치 시 설치 시 설치 시

LANmark-OF 실외용 DB 광케이블, 단일모드 G.652.D 9/125 96F, PE, 검정색, APAC 지역

Characteristics

구조적 특성	
Armour type	双层金属带
피복	폴리에틸렌
Sheath colour	검은색
기계적 특성	
Crush resistance (IEC 60794-1-E3)	300 N/cm
Maximum pulling force (IEC 60794-1-2-E1)	3000 N
Mechanical resistance to impacts (IEC 60794-1-E4)	10 impacts of 10 N.m
사용 특성	
Ambient installation temperature, range	0...40 °C
Minimum dynamic operating bending radius	378 mm
Minimum static operating bending radius	189 mm
操作温度范围	-40...70 °C
Storage temperature, range	-40...70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.