

Voice Cables APAC

- 25pr, 50pr, or 100pr
- Suitable for voice and low grade data
- Category 3 and Category 5 compliant

Voice grade cables are used to integrate telephony applications in the backbone of a LAN infrastructure. They are multipair twisted pair cables and exist in Category 3, Category 5 and Category 5e performance levels.



STANDARDS

ANSI/TIA-568-C.2
ISO/IEC 11801

Voice Cables APAC

CHARACTERISTICS

Construction characteristics

| | |
|---------------|-------|
| Outer sheath | LSZH |
| Type of cable | U/UTP |










Dimensional characteristics

| | |
|-----------------|----|
| Number of pairs | 25 |
|-----------------|----|

Usage characteristics

| | |
|----------|--------|
| Category | Cat. 3 |
|----------|--------|

Product list

| Aginode ref. | Country ref. | Name | Outer sheath | Type of cable | Number of pairs | Category |
|--|--------------|---|--------------|---------------|-----------------|----------|
|  N100.817N-3 | - | Voice U/UTP 25 pair AWG24 Cat 3 LSZH-FRT Orange reel | LSZH | U/UTP | 25 | Cat. 3 |
|  N100.819N-3 | - | Voice U/UTP 100 pair AWG24 Cat 3 LSZH-FRT Orange reel | LSZH | U/UTP | 100 | Cat. 3 |
|  N100.818N | - | Voice U/UTP 50 pair AWG24 Cat 3 LSZH Orange reel | LSZH | U/UTP | 50 | Cat. 3 |
|  N100.819N | - | Voice U/UTP 100 pair 24 AWG Cat 3 LSZH Orange Reel | LSZH | U/UTP | 100 | Cat. 3 |
|  N100.M22 | - | Voice U/UTP 25 pair AWG24 Cat 5e LSZH Orange 1000m reel | LSZH | U/UTP | 25 | Cat. 5e |
|  N100.817N | - | Voice U/UTP 25 pair AWG24 Cat 3 LSZH Orange reel | LSZH | U/UTP | 25 | Cat. 3 |
|  N100.837N | - | Voice U/UTP 25 pair AWG24 Cat 3 PE 1000m reel | PE | U/UTP | 25 | Cat. 3 |
|  N100.838N | - | Voice U/UTP 50 pair AWG24 Cat 3 PE 1000m reel | PE | U/UTP | 50 | Cat. 3 |
|  N100.818N-3 | - | Voice U/UTP 50 pair AWG24 Cat 3 LSZH-FRT Orange reel | LSZH | U/UTP | 50 | Cat. 3 |

 = Make to order,  = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.