LANmark-OF Female Plug&Play MTP-LC Module

- Play&Play module with 12 LC or 24 LC connections
- Available in LANmark-OF OM4 multimode and LANmark-OF OS2 singlemode
- Ultra low loss optical performance for multimode and low loss for singlemode
- Module can be easily mounted into Aginode' Plug&Play patch panel
- High density: 4 modules fit into 1U
- Straight or crossed wiring
- Plug&Play modules are pre-installed and 100 % factory tested



STANDARDS

ISO/IEC 11801

The Plug&Play system consists of 3 subcomponents: the Plug&Play modules, the MTP-MTP* Pre-Terms and the Plug&Play patch panel.

The central component is the pre-installed Plug&Play module. The MTP connector at the back of the module connects at once 12 fibres to the MTP-MTP Pre-Term. Inside the module the fibres are spread out towards the LC adaptors at the front.

Up to 4 Plug&Play modules can be installed quickly into the Plug&Play patch panel with push rivets. With these 4 modules a medium density of 48 LC or a high density of 96 LC connections within 1U can be achieved.

The insertion loss for the Plug&Play module is measured according to standard IEC 61300-3-45. The minimum return loss for a MTP connection is measured according to IEC 61300-3-6.

The modules are available with a straight and a crossed wiring.

For polarity methods A,B and C of standard TIA-568-C following modules and trunks need to be used:

- For a polarity method A implementation with a method A Pre-Term straight modules are used on both sides of the link.
- For a polarity method B implementation with a method B Pre-Term a straight cassette is used on one side of the link and a

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

crossed module on the other side of the link.
- For a polarity method C implementation with a method C Pre-Term straight modules are used on both sides of the link.

The Plug&Play module has standard unpinned (female) connectors. This matches perfectly with the pinned (male) connectors of the MTP-MTP Pre-Term.

Since all connectivity is factory terminated and tested installation times are short facilitating a quick deployment.

* MTP is a trade name of US Conec

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF Female Plug&Play MTP-LC Module

CHARACTERISTICS

Construction characteristics	
Connector type	LC
Fiber optic type	MultiMode 50/125
Wiring type	Straight
Dimensional characteristics	
Number of optical fibres	24

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name	Connector type	Fiber optic type	Wiring type	Number of optical fibres
	N441.5L24LCVFS	-	LANmark-OF Plug&Play Ultra Low Loss Module Female Straight 24 LC OM4 Violet	LC	MultiMode 50/125	Straight	24
	N441.5L12LCVFS	-	LANmark-OF Plug&Play Ultra Low Loss Module Female Straight 12 LC OM4 Violet	LC	MultiMode 50/125	Straight	12
	N441.5L12LC0FS	-	LANmark-OF Plug&Play Low Loss Module Female Straight 12 LC SM Blue	LC	SingleMode 9/125	Straight	12
	N441.5L24LC0FS	-	LANmark-OF Plug&Play Low Loss Module Female Straight 24 LC SM Blue	LC	SingleMode 9/125	Straight	24
	N441.5L12LCVFC	-	LANmark-OF Plug&Play Ultra Low Loss Module Female Crossed 12 LC OM4 Violet	LC	MultiMode 50/125	Crossed	12
	N441.5L24LCVFC	-	LANmark-OF Plug&Play Ultra Low Loss Module Female Crossed 24 LC OM4 Violet	LC	MultiMode 50/125	Crossed	24
	N441.5L12LC0FC	-	LANmark-OF Plug&Play Low Loss Module Female Crossed 12 LC SM Blue	LC	SingleMode 9/125	Crossed	12
	N441.5L24LC0FC	-	LANmark-OF Plug&Play Low Loss Module Female Crossed 24 LC SM Blue	LC	SingleMode 9/125	Crossed	24

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.