

Basement: Domino

- PON and P2P compatible
- Front patching between the fibres from operator network(s) and the ones from the riser
- Rear security for cable termination features
- Splitters integration
- Extension by adding boxes

The Domino basement boxes range has been especially designed for FTTH networks, to provide a modular solution for node interconnection between the external network and the building distribution network.

Stacking several Domino boxes enables to liaise between several operator networks and each subscriber.

The product range

The range is characterized by a universal housing, and various adaptable internal organisations according to the network configuration.

| Module height | Adapters maximum number | Splitters maximum number |
|---------------|-------------------------|--------------------------|
| 100mm | 24xSC | 6 splitters SOD |
| 165mm | 48xSC | 12 splitters SOD |
| 210mm | 72xSC | 6+12 splitters SOD |

A unique organizer performs all the cable termination features (splicing, splitting and/or patching, with overlengths management), depending on its cassettes layout.

An integrated swiveling tray allows the management of patchcords overlengths.


For standby fibres management, a version called "Storage" is also available.

Accessibility

The cable crimping is made outside of the box, and then the cable and its crimping plate are fixed in the box.

Quick door-dismantling and front patching enable easy access and identification for the connectors.

The product operation does not need any additional volume



STANDARDS

Aginode specification
Orange/France Telecom

after the product installation. Thus, its accessibility is guaranteed whatever the evolution of the installation environment.

Interconnection and security

Domino is fully compatible with equivalent modules on the market.

2 communication chimneys allow the fibres to go from a module to another one in the same stack.

The door is secured with a standard 8mm triangular key. The standard organizer has the same security system.


Domino Basement box

With front patching and swivelling tray to manage patchcords overlentghs, Domino basement boxes are easy to use without "spaghetti" issues (melting, node) on the right column.

Domino stack for Basement box use



Domino Splicing & Patching: version with splicing cassettes for G657 fibres for connection to riser or point to point



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.


Domino Splitting & Patching: version dedicated for use of splitter (SOD type) in case of point to multipoints/GPON network



Domino Splitting & Patching: view of cassette to splice trunks of splitters (compatible G652 fibre, up to 12 splices)



Domino Storage: version dedicated to use and storage of a preterminated riser cable



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Basement: Domino

CHARACTERISTICS

Construction characteristics

| | |
|-------------|---------------------|
| Colour | Light grey RAL 7035 |
| Cable entry | From left |
| Material | Polycarbonate |

Dimensional characteristics

| | |
|---|-----------|
| Depth | 150 mm |
| Height | 165 mm |
| Width | 450 mm |
| External diameter of the cable "D", range | 6...14 mm |

Mechanical characteristics

| | |
|-----------|---|
| IK Rating | 7 |
|-----------|---|

Usage characteristics

| | |
|---|-------------|
| Operating temperature, range | -25...70 °C |
| Adaptor | SC/APC |
| Fire resistant | UL 94 V0 |
| Number of ports | 5 |
| Minimum static operating bending radius | 15 mm |
| Locking system | Triangle |
| U.V resistance | Yes |
| Packaging | Box |
| Watertightness | IP 41 |

Resources

Documentation

[Domino Implementation Manual \(french\) pdf — 12.7 MB](#) Download 

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

| | Aginode ref. | Country ref. | Name |
|---|--------------|--------------|-------------------------------------|
| ☎ | 10237761 | - | Domino 165 - Storage |
| ☎ | 10236721 | - | Domino 100 - Splitting and patching |
| ☎ | 10236723 | - | Domino 165 - Splitting and patching |
| ☎ | 10243252 | - | Domino 100 - Splicing and patching |
| ☎ | 10236784 | - | Domino 165 - Splicing and patching |
| ☎ | 10236785 | - | Fixation with rails (H shape) |
| ☎ | 10243275 | - | Rails mounting kit |
| ☎ | 10243274 | - | Wall mounting kit |
| ☎ | 10238326 | - | 8mm triangle key |
| ☎ | 10261322 | - | Clamping kit for fanout devices |
| ☎ | 10261323 | - | Clamping kit for cable |
| ☎ | 10235293 | - | SC/APC 1:4 SOD splitter |
| ☎ | 10235334 | - | SC/APC 1:8 SOD splitter |

☎ = Make to order, 🏠 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.