S-Series Universal Cabinets

- 19-Inch, 42U cabinet
- Designed for general cabling system
- Ideal to host both copper and fiber cabling
- Robust metal construction
- Colour:Black



Aginode cabinets have been designed to install cabling products . The back door of cabinet is equipped double open door to save space; the cabinet side use material of high quality cold-rolled steel plate which can be conveniently disassembled without tools; the cabinet top and bottom are installed with fixed triangle, to strengthen the cabinet structure;aluminum magnesium alloy type material which is corrosion resistance, electrical conductivity, non magnetic, and with very good strength. The Cabinet is 2000mm high with supporting rod in cabinet. supporting frame is full 42U height. 2 or 4 fans are included depending on the cabinet depth.

STANDARDS

ISO/IEC 11801

Application

• ANSI/EIA-310-E
• The fixed column of the equipment is marked with the number of RMU by silk screen to facilitate the accurate positioning of the equipment
• Front door: Split perforated door with 80% of ventilation.
• Rear door: Split perforated door with 80% of ventilation.
• Cable management
Cabinet width: 600 mm ,with cable management bracket, without vertical cable manager
Cabinet width: 800 mm, with cable management bracket and vertical cable manager
• Top cable entry with cable brush
• Cabinet color :Black .
• Maximum static load: 1600kg
• Optional accessories:
Tray/division plate

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.