LANmark-OF UC PE (Unitube Steel Armoring)

UC optical fibre cables

- Outdoor in ducts or direct burial
- Corrugated steel tape armour
- Available in all fibres grades
- Provides full rodent protection





Description and Application

The construction is suitable for use outdoor in ducts and for direct burial. It consists of a corrugated steel tape armouring providing full rodent protection. It is surrounded by glass yarns. The cable has a HDPE outer jacket.
The loose tube design has a capacity of up to 24 fibres.
Diameter of the fibres is 250 um. Termination of these fibres is done with splicing of pigtails.
The cable is watertight due to the gel in the loose tube and the watertight glass yarns.

Characteristics

- Outdoor cable for installation in a duct or direct burial
- Designed for termination by splicing
- Central loose tube design
- Corrugated steel protection
- Waterproof structure, rodent resistant and UV-resistant
- Available in all fibre grades
- Available from 6-24 fibres

STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF UC PE (Unitube Steel Armoring)

CHARACTERISTICS

Construction characteristics

Construction type	Loose Tube
Fiber optic type	SM (G657.A1)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	Name
N164.UCPE06B	-	LANmark-OF UC 6x Singlemode 9/125 OS2 PE Black
N164.UCPE12B	-	LANmark-OF UC 12x Singlemode 9/125 OS2 PE Black
N164.UCPE24B	-	LANmark-OF UC 24x Singlemode 9/125 OS2 PE Black
N165.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM3 PE Black
N165.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black
N165.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM3 PE Black
N167.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM4 PE Black
N167.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM4 PE Black
N167.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.