LANmark WDZ-RYYP CU/LSZH/OS(TC)/LSZH Shielded Flame Retardant Flexible Cable

The LANmark Series of low-voltage cables are specialized cables designed for communication, signal transmission and low-voltage power supply of security equipment.
They are widely deployed in public security, monitoring projects, commercial buildings, residential buildings, smart homes and intelligent building systems.



Characteristic

- Copper Class 5
- Insulation of polyolefin, colored
- LSZH jacket
- Tinned Copper wire screen
- Nominal Voltage: U0/U=300/300V
- Temperature range: operation: -20°C ~ 70°C
  installation: 0°C ~ 50°C

Insulation color

Cores No.	color
2	Blue, Red
3	Blue, Red, Yellow/Green or Blue, Red, Green
4	Blue, Red, Green, Yellow/Green or Blue, Red, Green,Yellow
5	Blue, Red, Green,Yellow, Yellow/Green or Blue, Red, Green,Yellow, Black
6	Blue, Red, Green,Yellow, Black, Yellow/Green or Blue, Red, Green,Yellow, Black, Brown
7	Yellow jacket with number except Yellow/Green core.

Note: When there is a yellow/green ground wire in the core combination, The N-cord needs to add the suffix "G". The cross section will be using "G" to replace "x".

STANDARDS

IEC 60228
IEC 60754
IEC 61034
IEC 60332-1

TECHNICAL DATA

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

N – Code	Type	Cross section (mm²)	Insulation (mm)	Sheath (mm)	General OD. max	mix	Conductor Resistance 20°C / Ω/km	Insulation Resistance 70°C / MΩ.km
N10R13YWP205	WDZ-RYYP	2x0.5	0.5	0.6	5.7	7.7	39.0	0.013
N10R13YWP305	WDZ-RYYP	3x0.5	0.5	0.6	6.0	8.0	39.0	0.013
N10R13YWP405	WDZ-RYYP	4x0.5	0.5	0.6	6.6	8.6	39.0	0.013
N10R13YWP505	WDZ-RYYP	5x0.5	0.5	0.6	7.1	9.1	39.0	0.013
N10R13YWP605	WDZ-RYYP	6x0.5	0.5	0.8	7.7	9.7	39.0	0.013
N10R13YWP705	WDZ-RYYP	7x0.5	0.5	0.8	7.7	9.7	39.0	0.013
N10R13YWP805	WDZ-RYYP	8x0.5	0.5	0.9	8.6	10.6	39.0	0.013
N10R13YWP207	WDZ-RYYP	2x0.75	0.5	0.6	6.0	8.0	26.0	0.011
N10R13YWP307	WDZ-RYYP	3x0.75	0.5	0.6	6.4	8.4	26.0	0.011
N10R13YWP307G	WDZ-RYYP	3G0.75	0.5	0.6	6.4	8.4	26.0	0.011
N10R13YWP407	WDZ-RYYP	4x0.75	0.5	0.8	7.0	9.0	26.0	0.011
N10R13YWP507	WDZ-RYYP	5x0.75	0.5	0.8	7.6	9.6	26.0	0.011
N10R13YWP607	WDZ-RYYP	6x0.75	0.5	0.8	8.2	10.2	26.0	0.011
N10R13YWP707	WDZ-RYYP	7x0.75	0.5	0.8	8.2	10.2	26.0	0.011
N10R13YWP807	WDZ-RYYP	8x0.75	0.5	0.8	9.2	11.2	26.0	0.011
N10R13YWP210	WDZ-RYYP	2x1.0	0.6	0.6	6.8	8.8	19.5	0.010
N10R13YWP310	WDZ-RYYP	3x1.0	0.6	0.8	7.2	9.2	19.5	0.010
N10R13YWP410	WDZ-RYYP	4x1.0	0.6	0.9	7.9	9.9	19.5	0.010
N10R13YWP510	WDZ-RYYP	5x1.0	0.6	0.9	8.6	10.6	19.5	0.010
N10R13YWP610	WDZ-RYYP	6x1.0	0.6	1.0	9.6	11.6	19.5	0.010
N10R13YWP710	WDZ-RYYP	7x1.0	0.6	1.0	9.6	11.6	19.5	0.010
N10R13YWP810	WDZ-RYYP	8x1.0	0.6	1.0	10.7	12.7	19.5	0.010
N10R13YWP215	WDZ-RYYP	2x1.5	0.6	0.8	7.4	9.4	13.3	0.010
N10R13YWP315	WDZ-RYYP	3x1.5	0.6	0.8	7.8	9.8	13.3	0.010
N10R13YWP415	WDZ-RYYP	4x1.5	0.6	0.9	8.6	10.6	13.3	0.010
N10R13YWP515	WDZ-RYYP	5x1.5	0.6	1.0	9.6	11.6	13.3	0.010
N10R13YWP615	WDZ-RYYP	6x1.5	0.6	1.0	10.4	12.4	13.3	0.010
N10R13YWP715	WDZ-RYYP	7x1.5	0.6	1.0	10.4	12.4	13.3	0.010
N10R13YWP815	WDZ-RYYP	8x1.5	0.6	1.0	11.7	13.7	13.3	0.010
N10R13YWP225	WDZ-RYYP	2x2.5	0.7	1.0	8.9	10.9	7.98	0.009
N10R13YWP325	WDZ-RYYP	3x2.5	0.7	1.0	9.4	11.4	7.98	0.009
N10R13YWP425	WDZ-RYYP	4x2.5	0.7	1.0	10.4	12.4	7.98	0.009
N10R13YWP525	WDZ-RYYP	5x2.5	0.7	1.1	11.5	13.5	7.98	0.009
N10R13YWP625	WDZ-RYYP	6x2.5	0.7	1.1	12.6	14.6	7.98	0.009

Note: When there is a yellow/green ground wire in the core combination, The N-cord needs to add the suffix "G". The cross section will be using "G" to replace "x".

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	Name
N10R13YWP707	-	LANmark WDZ-RYYP 7x0.75mm² CU/LSZH/OS(TC)/LSZH, Shielded Flame Retardant Flexible Cable,Black

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.